



I. Product Description

CRC Aviation Super Degreaser utilizes technology that combines the power of a high performance, heavy duty cleaner/degreaser with the safety that modern regulations demand. **Aviation Super Degreaser** is non-chlorinated, non-conductive, non-corrosive, non-staining and has no flash or fire point. It quickly dissolves grease, oil and sludge for more efficient operation of mechanical equipment. **Aviation Super Degreaser** evaporates rapidly and leaves no residue.

II. Applications

Recommended for the effective removal of grease, oil, corrosion and sludge from metal parts, ground support equipment, electric motors, spark plugs and valves, oxygen handling equipment, air tools, mechanical brakes, clutches, chains, wire ropes, motors, dies, molds, parts, bearings, generators and compressors.

III. Features & Benefits

- **Contains No Chlorinated Solvents.** Formula offers performance of 1,1,1-Trichloroethane without the associated risks.
- **Contains No HAP's.**
- **Meets the requirements of CSD-1, Category II and Boeing D6-17487 with the exception of acrylic crazing.**
- **No Flash or Fire Point.** Significantly reduces the risk of fire caused by incidental contact with live electrical equipment or solvents trapped by insulating materials.
- **Fast Evaporating, No Residue.** Minimizes downtime associated with "clean-in-place" cleaning methods.
- **Chemically stable, non-conductive and non-corrosive.**
- **No Class I or Class II Ozone Depleting Chemicals.** Alternative to 1,1,1-Trichloroethane products.
- **M.S.D.[L.]™ Material Safety Data Label** provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**

IV. Physical Properties without propellant

Flash Point	None	Boiling Point	160°F
Odor	Strong	Solubility	0.25g/100mL @68°F
Appearance	Colorless liquid	% Volatile	100
Vapor Density	4.30	Specific Gravity	1.33 @25°C
Vapor Pressure	112 mm @20°C	Propellant	CO ₂
Sara Title III, Sect. 313 Chemicals	Yes	VOC Content (Fed)	1265 g/L
Prop 65	Yes		

V. Specifications and Approvals

- Meet the requirements of CSD-1, Category II and Boeing D6-17487 with the exception of acrylic crazing.

VI. Performance Characteristics

ASTM D-1130 (KB Value)	125
ASTM D-877 (Dielectric Strength)	26,800 volts

VII. Directions

- Remove mechanical plates, covers, etc. to expose equipment interior.
- For best results, remove heavy deposits of contaminants by scraping with a knife or wire brush.
- Spray until clean.
- Use extension tube for hard-to-reach areas.
- Allow equipment to fully dry and vent before using.
- **Do not use on acrylic and polycarbonate plastics such as LEXAN®. If in doubt, contact the manufacturer of the equipment. MAY ALSO BE HARMFUL TO OTHER PLASTICS.**
- Not for use on sensitive electronics, computers, tape decks or VCRs. Use a CRC precision cleaner instead.
- **For personal safety, do not use while equipment is energized.**

VIII. Package Description

Part Number	Container Size
10905	20 oz Aerosol

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

X. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260