



I. Product Description

CRC Rust Proof Primer Spray Paint is a fast drying surface sealer that provides maximum rust protection and better adhesion for application of **CRC Rust Proof Enamel**. For maximum adhesion, sand lightly with fine sandpaper or steel wool prior to applying finish coat.

II. Applications

Recommended for use on bare metal or wood, machinery and structural steel.

III. Features & Benefits

- **Reduced Overspray**
- **Fast Drying** and Sag Free
- **Excellent hiding power.**
- **S.D.[L.][®]-Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**
- **20 oz. aerosol** can size.
- **Inhibits rust and effective against chemicals**

IV. Physical Properties with propellant

Resin System	Phenolic	% Volatile	51
Flash Point	<0°F TCC	Heat Resistance	250°F
Odor and Appearance	Aromatic	Propellant	Hydrocarbon
Vapor Density	Heavier than air	Solids Content	23%
VOC Content (Fed) (Wt.)	60% maximum		
Sara Title III, Sect. 313 Chemicals	Yes		
Prop 65	Yes		

V. Performance Characteristics

Dry Time, to touch	5 minutes
Dry Time, to topcoat	30 minutes
Square Foot Coverage	25 to 40 square feet

VI. Directions

- Shake vigorously for at least one minute after rattling of mixing ball is heard. Shake intermittently during application.
- For best results, spray between 50°F to 90°F.
- Surface to be painted should be clean and dry. Remove dirt, grease, oil, rust, scale and other contaminants.
- Mask areas not to be sprayed to protect from overspray.
- Hold can 12 to 16 inches from surface. Press spray button firmly. Do not apply with continuous spray. Use back and forth motion, keeping can in a level line with surface.
- Apply topcoat after 30 minutes.
- To prevent valve from clogging after spraying, turn can upside down and press sprayhead for about 3 seconds. This will clean paint from siphon tube and valve. If spray button is clogged, remove from can and run knife edge through tiny slit at end of spray button stem. Clear spray button orifice by inserting pin. Do not insert pins or other sharp objects into valve opening of can.

VII. Package Description

18150	Gray	20 OZ. Aerosol Can
-------	------	-----------------------

VIII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn.

Some state and local agencies may require that aerosol paints be sold from locked cages or other specialized displays in order to conform to local anti-graffiti regulations. Check with local authorities to ensure compliance with existing regulations. CRC can provide locked cages to aid in conformance to anti-graffiti legislation.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.

CRC Industries
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260