



I. Product Description

Salt Terminator® Engine Flush, Cleaner & Corrosion Inhibitor cleans and protects anything exposed to salt, saltwater, salt air and road salt. It dissolves salt and leaves a protective coating to inhibit corrosion. Essential use as a motor flush for marine engines in both saltwater and freshwater environments.

II. Applications

Use as a flush for marine engine cooling systems and heat exchanges. Cleans & Protects boats, PWCs, trailers, gear, fishing tackle, autos, RVs, trucks, tools, motorcycles, ATVs, bicycles, patio furniture & more.

III. Features & Benefits

- Water Based
- Biodegradable and Non-Toxic
- Safe for use on fiberglass, steel, aluminum, glass, magnesium, isinglass, wood, chrome plastic and rubber.

IV. Physical Properties without propellant

Flash Point	None	Boiling Point (initial)	212°F/100°C
Odor	None	Solubility	Soluble
Appearance	Blue Liquid	pH:	9.33
Vapor Density	Not Determined	Specific Gravity	1.10
VOC Content (Fed)	0.28 %	Vapor Pressure	Not Determined
Sara Title III, Sect. 313 Chemicals	Sodium Nitrite (13%)	Freezing Point	32°F/0°C
Prop 65	Diethanolamine, Cocamide DEA		

V. Specifications and Approvals

None

VI. Performance Characteristics

Bellcore Test (Plastic Compatibility)	Yes
---------------------------------------	-----

VII. Directions

To Flush Outboard / Inboard / Outdrive / Cooling Systems & Heat Exchangers:

- Salt Terminator mixer is required. Attach mixer to garden hose. Remove reservoir cup, fill with Salt Terminator and reinstall. Connect other end of mixer to flushing apparatus and turn on water. Flush motor for 2-5 minutes.

To Remove Salt & Protect Surfaces:

- Attach mixer to garden hose. Remove reservoir cup, fill with Salt Terminator and reinstall. Connect other end of mixer to garden hose spray nozzle. Turn on fresh water. Spray on any surface and rinse.

To Soak Gear & Equipment:

- Mix 4 ounces of concentrate per 1 gallon of water in a pail. Soak gear or equipment and scrub if necessary. Rinse with water.

VIII. Package Description

Part Number	Container Size
SX10	12 fl oz
SX22	22 fl oz Trigger Bottle
SX32	32 fl oz
SX32M	32 fl oz with Mixer
SX128	1 Gallon
SX55	55 Gallon

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

X. Special Use Warnings

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Safety Data Sheet.

PRODUCT WARRANTY: CRC offers a conditional warranty on this product for the period of 2 years from the date of manufacture.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Sta-Lube Products Division
Customer Service: (800)272-8963

Warminster, PA 18974
CRC On-Line: (215)442-6260