



I. Product Description

Power Lube® Multi-Purpose Lubricant is a fast acting lubricant that finds and stops squeaks. Power Lube® penetrates deep through rust and scale to loosen frozen parts and lubricates and protects metal surfaces without leaving a sticky residue. Power Lube® displaces moisture, prevents corrosion, and cleans light oils. Power Lube® is safe on most plastics.

II. Applications

Recommended for use on hinges, speedometer cables, seat slides, door locks, distributors, power antennas, wheels, lug nuts, battery terminals, air tools, switches, computers, clocks, firearms, fishing reels, bicycles, etc.

III. Features & Benefits

- **All-In-One Formula.** Fills needs for lubricant, penetrant, light duty cleaner and corrosion inhibitor in one product.
- **Displaces Moisture.** Prevents corrosion to improve equipment life and performance.
- **360° Valve.** Product can be sprayed from any position -- even upside down.
- Available in **9 oz. and 11 oz. aerosol** cans.
- Available in bulk in **1 gallon and 5 gallon pails** and **55 gallon drums**.

IV. Physical Properties without propellant

Flash Point	178°F TCC		Boiling Point	380°F (initial)	
Odor	Mint		Solubility	Neg. in water	
Appearance	Amber Liquid		Specific Gravity	0.8199	
Vapor Density	>2 (air=1)		Propellant	CO ₂	
VOC Content (Fed)	Aerosol 313.2 g/L	Bulk 321.4 g/L	VOC %	Aerosol 38.2%	Bulk 39.2%
Sara Title III, Sect. 313 Chemicals	No		Prop 65	No	

V. Performance Characteristics

Type of Film	Non-drying
ASTM D-56 (Flash Point)	178°F (TCC)
Corrosion Inhibitor	Indoor Only/up to 9 months Ferrous & Non-Ferrous Metals

VI. Package Description

Part Number	Container Size
05005	9 oz Aerosol
05006	11 oz Aerosol
05007	1 Gallon
05009	5 Gallon
05011	55 Gallon

VII. Directions

- Read entire label before using this product.
- Corrosion: Apply liberally and allow to penetrate for a few minutes. Tap part gently to set up vibration.
- Lubrication: Spray in light, even coats to lubricate and protect metal surfaces.
- Moisture: To displace moisture, spray wet surfaces until run-off is clear and moisture-free.
- Do not apply while equipment is energized.

VIII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state, and federal regulations.

IX. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Automotive Products Division
Customer Service: (800)272-8963

Warminster, PA 18974
CRC On-Line: (215)442-6260