



## I. Product Description

**Gasket Remover** is a solvent-based, high strength cleaner that helps remove baked-on fiber gaskets, gasket adhesives and sealants. It quickly dissolves and aids in the removal of paints, lacquers, adhesives and varnishes.

## II. Applications

Recommended for the effective removal of conventional and formed-in-place gaskets on motors, pumps, and flanges. Aids in dissolution and removal of paints, lacquers, adhesives and varnishes. Gasket Remover removes graffiti from metal and stone.

## III. Features & Benefits

- **Works Quickly.** Softens and eases removal of gaskets, gasket cements, and sealants.
- **Loosens Carbon Deposits.**
- **Excellent Paint, Varnish and Graffiti Remover.** Aggressive cleaner works efficiently.
- Available in **16 oz. aerosol** for controlled application of product.

## IV. Physical Properties without propellant

<b>Flash Point</b>	56°F SETA	<b>Solubility</b>	Soluble in Water
<b>Odor</b>	Fragrant Solvent	<b>Specific Gravity</b>	0.7419
<b>Appearance</b>	Light Gray Liquid	<b>Propellant</b>	Hydrocarbon
<b>Vapor Density</b>	>1 (air=1)	<b>VOC %</b>	47.5%
<b>Sara Title III, Sect. 313 Chemicals</b>	Yes	<b>VOC Content (Fed)</b>	352.4 g/L
<b>Prop 65</b>	Yes		

## V. Packaging Description

<b>05021</b>	12 wt oz
--------------	----------

## VI. Directions

- Wear eye protection and rubber gloves or other non-porous hand protection.
- Protect painted surfaces from overspray, as product will dissolve paint.
- Gasket removal: spray liberal coating on gasket and allow to set for 5 - 10 minutes. Remove with putty knife.
- Paint and graffiti removal: spray liberal coating on painted surface. Allow to dry and brush with a stiff bristled brush.
- Adhesive removal: apply liberal coating and allow to work for 2 - 3 minutes. Wipe with rag or wiper. Repeat application for thick buildup areas.
- Do not use on energized equipment.

## VII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state, and federal regulations.

## VIII. Special Use Warnings

### Aerosol Cans

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

### General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Safety Data Sheet.

**DISCLAIMER:** This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.  
Technical Service: (800)521-3168

Automotive Products Division  
Customer Service: (800)272-8963

Warminster, PA 18974  
CRC On-Line: (215)442-6260