



I. Product Description

White Lithium Grease is a high-purity, high-quality NLGI Grade 2 white lithium-based grease that provides superior lubrication and durability in any weather and most temperatures. This versatile grease is designed for light duty applications requiring a long grease life. **White Lithium Grease** contains oxidation inhibitors to counter corrosion, and protects with a tough, high viscosity film.

II. Applications

Recommended to lubricate hinges, latches, overhead door tracks, open gears and chains, cables, slide conveyors, guide rails, cams and pistons. Excellent as a break-in lubrication for bearings. Also used for general purpose lubrication and corrosion protection for machinery, tools, and equipment.

III. Features & Benefits

- **Heat and Water Resistant.** Provides lasting lubrication and durability under stressful conditions.
- **Rust & Oxidation Inhibitors.** For superior metal protection.
- **High Purity, NLGI Grade 2** white lithium based-grease.
- **Non-Conductive.**
- Available in **16 oz. aerosol** for controlled application of product.

IV. Physical Properties without propellant

Flash Point	<20°F TCC	Boiling Point	140°F
Odor	Solvent	Solubility	Not soluble in water
Appearance	Off white grease	Vapor Density	>1 (air=1)
Specific Gravity	0.6257	Propellant	Hydrocarbon
Sara Title III, Sect. 313 Chemicals	Yes	VOC Content (Fed)	531.8 g/L
Prop 65	No	VOC %	85%

V. Packaging Description

05037	10 wt oz
-------	----------

VI. Performance Characteristics

Drop Point (ASTM D-2268)	350°F min.
Pour Point (ASTM D-97)	0°F
Viscosity-Base Oil @ 100°F	720-800 SUS
Operating Temperature Range	0° to 300°F
Wheel Bearing Leakage (ASTM D-1263)	5 grams
Timken OK Load (ASTM D-2509)	25 lbs.

VII. Directions

- Do not apply while equipment is energized.
- Shake well before use.
- Clean area to be lubricated.
- Spray in light, even coats.
- Use extension tube for hard-to-reach areas.
- Do not mix greases of different base types.

VIII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Automotive Products Division
Customer Service: (800)272-8963

Warminster, PA 18974
CRC On-Line: (215)442-6260