



I. Product Description

Battery Terminal Protector is designed to protect battery terminals from corrosion, the leading cause of battery failure, and to maintain the battery's peak performance level. **Battery Terminal Protector** provides a soft, lead-free protective coating that keeps moisture, salts and road grime from corroding metal contacts. Maximizes performance, provides long lasting protection and extends battery life.

II. Applications

Recommended for use on battery posts, terminals, hold-downs and casings used in vehicles, boats, handling equipment and uninterrupted power supplies (UPS), and used for computer, security and emergency back-up systems.

III. Features & Benefits

- **Soft, Flexible Film.** Completely encapsulates exposed surfaces. Will not become brittle, crack or peel. Withstands excessive wear caused by vibration of moving vehicles.
- **Red Color.** Provide easy visual inspection of application.
- **Lead-free.** Promotes safer work environment.
- **Contains No Known Ozone Depleting Chemicals.** Offers effective performance while complying with the EPA regulations on the use of ozone depleting chemicals.

IV. Physical Properties without propellant

Flash Point	<0°F TCC	Boiling Point	140°F
Odor	Solvent	Solubility	Neg. in water
Appearance	Dark Red, viscous	VOC %	78.3%
Vapor Density	>1 (air = 1)	Specific Gravity	0.744
VOC Content (Fed)	582.6 g/L	Propellant	Hydrocarbon
Sara Title III, Sect. 313 Chemicals	Yes		
Prop 65	Yes		

V. Packaging Description

05046	7.5 wt oz
-------	-----------

VI. Performance Characteristics

Type of Film	Soft, visible, viscous film
--------------	-----------------------------

VII. Directions

- Always read entire label before using product.
- Shake can well before using.
- Clean away existing corrosion with CRC® Battery Cleaner with Acid Indicator, item #05023.
- Apply an even coat to freshly cleaned hold-downs, bolts, brackets and terminals.
- For preventive maintenance, reapply when red film turns clear or every four months.
- When finished spraying, clean valve by turning can upside down and depressing actuator until only propellant escapes.
- Do not apply while equipment is energized.
- Do not allow can to touch battery terminals.

VIII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Product is extremely flammable and should be kept from all flames and other ignition sources. Extinguish all flames, pilot lights, and heaters .

Aerosol Cans

Do not puncture, incinerate or store above 120°F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Automotive Products Division
Customer Service: (800)272-8963

Warminster, PA 18974
CRC On-Line: (215)442-6260