



## I. Product Description

**Sta Lube® Air Tool Oil** is formulated using a quality base lubricant blend and high-tech additive system which keeps pneumatic equipment operating longer with greater power and less down time.

## II. Applications

To be used in pneumatic equipment such as:

- Impact wrenches, air ratchets, sanders, grinders, air motors, hammers, drills, etc.

## III. Features & Benefits

- Picks up and expels moisture into exhaust air.
- Reduces rust, varnish, sludge and acids.
- Provides smoother operation with increased torque.
- Extreme pressure additives ensure long tool life.

## IV. Physical Properties

|                                     |                   |                         |            |
|-------------------------------------|-------------------|-------------------------|------------|
| Flash Point                         | ≥320 °F COC       | Boiling Point (initial) | >600 °F    |
| Odor                                | Faint Petroleum   | Solubility              | Negligible |
| Appearance                          | Dark amber liquid | % Volatile              | Negligible |
| Vapor Density                       | > Air             | Specific Gravity        | .85 - .95  |
| Prop 65                             | No                | Vapor Pressure          | Negligible |
| Sara Title III, Sect. 313 Chemicals | No                |                         |            |

## V. Specifications and Approvals

|                                   |       |
|-----------------------------------|-------|
| ASTM D-92 Flash Point, °F         | ≥ 320 |
| ASTM D-445 Viscosity @ 40° C, cSt | 25-26 |

## VI. Directions

Fill to manufacturer recommendations.

## **VII. Disposal**

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

## **VIII. Special Use Warnings**

### **General**

Use only in well-ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

**DISCLAIMER:** This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

*CRC Industries, Inc.  
Technical Service: (800)521-3168*

*Sta-Lube Products Division  
Customer Service: (800)272-8963*

*Warminster, PA 18974  
CRC On-Line: (215)442-6260*