



1. Product Description

Sta Lube® SAE 140 Multi-Purpose Hypoid Gear Oil is a light duty gear oil with extreme pressure additives perfect for auto, truck and bus standard transmissions and differentials.

II. Applications

For use in auto, truck and bus standard transmissions and differentials requiring API/GL-3 and GL-4 oils.

III. Features & Benefits

- Contains anti-wear and extreme pressure properties.
- Protects against oxidation, rust, corrosion and foaming.
- Provides film strength needed in the heavy-duty service of industrial drives, worm and hypoid gear sets.
- Not corrosive to copper, bronze or other non-ferrous alloy bearings and bushings.
- Available in quart, 1 gallon and 5 gallon containers.

IV. Physical Properties

Flash Point	≥450 °F COC	Boiling Point (initial)	ND
Odor	Faint Petroleum	Solubility	Insoluble
Appearance	Clear Amber Liquid	% Volatile	Negligible
Vapor Density	> Air	Specific Gravity	.92
Prop 65	No	VOC	3%
Sara Title III, Sect. 313 Chemicals	No		

V. Specifications and Approvals

Meets Specifications US Steel 224 and AGMA 250.03.

ASTM D-92 Flash Point, °F	≥ 450° F
ASTM D-97 Pour Point, °F	-21° F
ASTM D-445 Viscosity @ 100° C, cSt	27.5

VI. Directions

Fill to manufacturer recommendations.

VII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

VIII. Special Use Warnings

General

Use only in well-ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure; review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Sta-Lube Products Division
Customer Service: (800)272-8963

Warminster, PA 18974
CRC On-Line: (215)442-6260