



1. Product Description

Sta Lube® Universal 2 Cycle Oil for Air Cooled Engines is specially formulated to protect and extend engine service life using a quality base lubricant and high-tech additive system.

II. Applications

Recommended for engines of 25 horsepower or less such as:

- 2-Cycle Motorcycles, Motor Scooters, Mopeds and Mini-Bikes
- Lawn Mowers, Chain Saws and Garden Equipment
- Power Generators
- Auxiliary Pumps and Refrigeration Equipment

III. Features & Benefits

- Quick stable mixing.
- Protects against corrosion, rust and high heat.
- Clean burning – minimal smoke.
- For injector or pre-mix systems.
- Minimizes:
 1. Plug fouling
 2. Bearing heat
 3. Port plugging
 4. Ring sticking
 5. Carbon deposits
 6. Piston seizure.
- Available in 15 and 32 fluid ounce bottles.

IV. Physical Properties

Flash Point	>150 °F COC	Boiling Point (initial)	>300 °F
Odor	Faint Petroleum	Solubility	Negligible
Appearance	Blue oily liquid	% Volatile	15 – 20%
Vapor Density	> Air	Specific Gravity	.88 - .90
Prop 65	No	Vapor Pressure	Negligible
Sara Title III, Sect. 313 Chemicals	No		

V. Specifications and Approvals

ASTM D-92 Flash Point, °F	≥ 150
ASTM D-445 Viscosity @ 100° C, cSt	8.5-9.5

VI. Directions

- Use and mix according to equipment manufacturer recommendations.
- For 32:1 mix, add 4 ounces to 1 gallon of gasoline.
- For 40:1 mix, add 8 ounces to 2.5 gallons.

VII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

VIII. Special Use Warnings

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Sta-Lube Products Division
Customer Service: (800)272-8963

Warminster, PA 18974
CRC On-Line: (215)442-6260