



1. Product Description

Sta Lube® Power Steering Fluid is specially formulated to meet requirements for power steering units in General Motors, Ford, American Motors, later model Chrysler and most import autos (excluding Honda and Audi. For Honda, Acura, and Audi applications, use SL2651).

II. Applications

Formulated as performance equivalent to:

- General Motors Part No. 1050017
- Ford Motors Spec. No. ESW-M2C128-D
- American Motors Part No. 8993342
- Chrysler Part No. 4318056, Spec. No. MS5931F (For pre '89 models, use Sta Lube Product No. SL 2641.)

III. Features & Benefits

- Maintains proper seal swell/shrinkage.
- Increases hydraulic hose life.
- Provides oxidation resistance, which prevents rust and corrosion.
- Prevents foaming.
- Assures uniform performance over wide range of temperature conditions because of high viscosity index.
- Available in 15 fluid ounce and 1 gallon containers.

IV. Physical Properties

Flash Point	>350 °F COC	Boiling Point (initial)	>600 °F
Odor	Faint Petroleum	Solubility	Negligible
Appearance	Clear Red Liquid	% Volatile	Negligible
Vapor Density	> Air	Specific Gravity	.85 - .87
Prop 65	No	Vapor Pressure	Negligible
Sara Title III, Sect. 313 Chemicals	No		

V. Specifications and Approvals

ASTM D-92 Flash Point, °F	≥ 350
ASTM D-445 Viscosity @ 100° C, cSt	7.0-7.6

VI. Directions

Consult owner's manual to assure correct fluid and proper reservoir levels. May be added to existing fluid or for complete fill.

VII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

VIII. Special Use Warnings

General

Use only in well-ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure; review this product's Material Safety Data Sheet.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Sta-Lube Products Division
Customer Service: (800)272-8963

Warminster, PA 18974
CRC On-Line: (215)442-6260