



Pipe Thread Sealant

Thread Sealing Compound with PTFE

CRC Pipe Thread Sealant is a non-toxic, non-drying thread sealing compound consisting of a blend of non-melting grease, PTFE particles and other inert solid fillers, engineered to produce a leak-proof seal. Does not contain lead, graphite, molybdenum disulfide, or clay fillers.

Non-Hardening • Non-Toxic • Prevents Corrosion

- Holds Pressure to 8,000 PSI
- Positive Seal
- Convenient Brush Top
- Non-Hardening Formula
- Contains PTFE



CRC Pipe Thread Sealant can be used to seal all threaded joints in plastic, aluminum, monel, or stainless steel lines against water, natural gas, LPG, gasoline and other services. It is also effective on connections, pipe bungs, bolts, flange seals, and as a gasket-parting compound.

CRC Part #	Color	Usable Temperature Range	NLGI Grade	Penetration ASTM D-217	100 HR 5% Salt Spray ASTM B-117	Flash Point ASTM D-92
SL35401	White	-35°F to 550°F	1	310-340 mm	No Rust	400°F

CAUTION: DO NOT USE ON OXYGEN SYSTEMS



Your Best Solution™

Customer Service: 800-272-4620
 Technical Assistance: 800-521-3168
www.crcindustries.com/ei



CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.

©2015 CRC Industries, Inc.

10399-SS PDF