

# CRC® 2-26® Multi-Purpose Precision Lubricant

**DIRECTIONS:** Read entire label before using this product.

**1. Do not apply while equipment is energized. Allow to dry at least 4 to 6 hours before energizing.** 2. Spray light, even coat to protect surfaces and to seal out moisture. 3. Apply liberally to loosen rusted parts. 4. Spray wet surfaces until run-off is clear and moisture free.

**Danger:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.



**Precautionary Statements:** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

**First Aid:** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Contains Hydrotreated light distillates (64742-47-8), Light mineral oil (8042-47-5), n-Butyl stearate (123-95-5), Carbon dioxide (124-38-9), Petrolatum (8009-03-8) and Sorbitan monooleate (68910-94-1). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

**Electrical Shock Hazard:** This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

©2016 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974      CRC# 591B/C 16A  
www.crcindustries.com      Made in U.S.A.  
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS)



## 2-26® Multi-Purpose Precision Lubricant

Plastic Safe  
Improves Electrical Properties



Nonfood Compounds  
Program Listed  
Category Code: H2  
Reg.# 017224



*Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite [www.crcindustries.com](http://www.crcindustries.com).*

**DANGER: FLAMMABLE.  
HARMFUL OR FATAL IF  
SWALLOWED. CONTENTS  
UNDER PRESSURE.  
KEEP AWAY FROM CHILDREN.**  
Read warnings on back panel.

**No. 02004**  
**Net Wt.**  
**5 oz (142 g)**

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty.

## Identification

2-26© Multi-Purpose Precision Lubricant

Product code 02004

Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive,  
Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

Issue date 1/28/2016

CRC# 591B/C

Ver. # 03

## Ingredients

Chemical name	CAS number	TWA	%	SARA 313
Hydrotreated light distillates	64742-47-8	100 mg/m <sup>3</sup>	60 – 70	No
Light mineral oil	8042-47-5	5 mg/m <sup>3</sup>	10 – 20	No
n-Butyl stearate	123-95-5	10 mg/m <sup>3</sup>	3 – 5	No
Carbon dioxide	124-38-9	9000 mg/m <sup>3</sup>	1 – 3	No
Petrolatum	8009-03-8	5 mg/m <sup>3</sup>	1 – 3	No
Sorbitan monooleate	68910-94-1	None	1 – 3	No

## Hazards

**Health:** Aspiration hazard (Category 1)

**Ingestion** May be fatal if swallowed and enters airways.

**Inhalation** Prolonged inhalation may be harmful.

**Skin contact** Prolonged skin contact may cause temporary irritation.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Carcinogenicity** Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

**Chronic effects** Prolonged inhalation may be harmful.

**Physical:** Flammable aerosols (Category 1)

Gases under pressure (Compressed gas)

Product is extremely flammable. Vapors may accumulate in a confined space and create a flammable atmosphere. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. Do not puncture or incinerate.

## First-aid measures

**Inhalation** Move into fresh air and keep calm. If breathing is difficult, get medical attention.

**Skin contact** Remove contaminated clothing and wash skin with soap and water. If irritation occurs, get medical attention.

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Call a physician or poison control center immediately. DO NOT induce vomiting.

**Advice for doctor** Treat symptomatically. The effects might be delayed.

## Personal Protection

**Eye/face** Wear safety glasses with side shields (or goggles).

**Skin** Use protective gloves such as nitrile or neoprene. Wear appropriate clothing to prevent skin contact.

**Respiratory protection** If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

## Safe Handling

**General** Beware of the fire/explosion danger. Do not smoke and do not spray near any sources of ignition or energized equipment. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid contact with skin and eyes. Avoid breathing mist or vapor. Wash after handling. Avoid discharge into drains, water courses or onto the ground.

**Fire** Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO<sub>2</sub>). Firefighters must wear self-contained breathing apparatus and full protective clothing. Containers should be cooled with water to prevent vapor pressure build up.

**Spill clean-up** Remove sources of ignition. Ventilate the area. Prevent entry into waterways or sewers. Wipe up with absorbent material and transfer to disposal container.

**Storage** Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight.

**Disposal** The dispensed liquid product is not a RCRA hazardous waste. Empty container can be recycled.

**Transport** UN1950, Aerosols, flammable, 2.1, limited quantity

## Properties

**Appearance** Amber liquid.

**Odor** Mild petroleum.

**Melting point/freezing point** -56 °F (-49 °C)

**Initial boiling point** Not available.

**Flash point** 200 °F (93 °C) Tag Closed Cup

**Explosive limit - lower (%)** 0.6 %

**Explosive limit - upper (%)** 5.5 %

**Evaporation rate** Slow

**Vapor pressure** 1558 hPa

**Vapor density** > 1 (Air = 1)

**Relative density** 0.84

**Solubility(ies)** Negligible in water

**Auto-ignition temperature** 392 °F (200 °C)

**VOC (Weight %):** 0%

**Stability** Stable

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition products** Carbon oxides.