


Read entire label before
using this product.



Nonfood Compounds Program
Listed (H2) (#017223)

Electrical Grade 2-26[®] Plastic Safe Multi-Purpose Precision Lubricant



02009

Part No. 02009


NET WEIGHT 34 lb (15.4 kg)



DANGER
May be fatal if swallowed and enters airways.

PRECAUTIONARY STATEMENTS

Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Store locked up. Do not store container above 100 °F/38 °C. Dispose of contents/container in accordance with local/regional/national regulations.



HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	1	REACTIVITY	0
FLAMMABILITY	1	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

- Improves electrical properties
- Lubricates, penetrates, cleans and protects all metal surfaces
- Safe for use on all plastics
- Displaces moisture from wet or flooded equipment

Contains Hydrotreated light distillates (64742-47-8), Light mineral oil (8042-47-5), n-Butyl stearate (123-95-5), Fatty acid dimers (61788-89-4) and Petrolatum (8009-03-8).

©2016 CRC Industries, Inc.

885 Louis Dr.

Warminster, PA 18974

800-521-3168 (Technical information)

800-272-4620 (Customer Care)

215-442-6260 (SDS)

www.crcindustries.com

16A CRC#591B/C Made in U.S.A.

FOR EMERGENCIES CALL CHEMTREC

1-800-424-9300

DATE
CODE:



0 78254 02009 9

FIRST AID
If swallowed: Immediately call a poison center/doctor.
Do NOT induce vomiting.

Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Do not apply while equipment is energized.