

Read entire label before using this product.



Seal Coat® Clear Urethane Coating

Part No. 02051



NET WEIGHT 34 lbs. (15.5 kg)



DANGER

Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility.

PRECAUTIONARY STATEMENTS

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations.

FIRST AID

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

37.95% of the mixture consists of component(s) of unknown acute inhalation toxicity.

This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Do not apply while equipment is energized.

- A conformal polyurethane coating that insulates electrical equipment and seals out water and moisture.
- Clear formula allows for visualization of equipment.
- Dries quickly to a hard, durable, flexible and non-conductive film.
- DIRECTIONS: Apply a thin even coat by brushing or spraying. Additional coats for heavy film can be applied when first coat is dry.

Contains Acetone (67-64-1), Hydrotreated light naphtha (64742-49-0), Xylene (1330-20-7), 2-Methylpentane (107-83-5), Propylene glycol monomethyl ether acetate (108-65-6), Ethylbenzene (100-41-4) n-Hexane (110-54-3) and Methyl ethyl ketoxime (96-29-7).

©2014 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical information)
800-272-4620 (Customer Service)
215-442-6260 (SDS)
www.crcindustries.com
14A CRC#505A/B Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300



DATE
CODE:

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	2*	REACTIVITY	0
FLAMMABILITY	3	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4