

Warning: Contains gas under pressure; may explode if heated.



Precautionary Statements: Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49°C/120°F. Observe good industrial hygiene practices. Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations. **First Aid:** Wash hands after handling.

Contains Polydimethylsiloxane (63148-62-9), Amorphous fumed silica (112945-52-5) and Nitrogen (7727-37-9). For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Do not touch can to live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from electrical shock.



Dielectric Grease Compound

Protects Electrical Contacts

Lubricates and Seals O-Rings

Prevents Rust and Corrosion



Nonfood Compounds Program Listed
Category Code: H1 Reg.# 151609

WARNING:
CONTENTS UNDER
PRESSURE. KEEP AWAY
FROM CHILDREN.

Read warnings on back panel.



No. 02085
Net Wt.
3.3 oz. (94 g)

DIRECTIONS: Read entire label before using this product.

1. For personal safety, do not apply while equipment is energized.
2. Shut off power supply, be sure all stored power is drained from system and allow hot surfaces to cool before using this product.
3. Clean surfaces, connectors and contacts with a CRC Precision Cleaner.
4. Remove cap, pull tab, then adjust cap following min/max arrow to control grease width. Press handle to apply.
5. Squeeze trigger to dispense product. Coat areas requiring lubrication or protection.

©2015 CRC Industries, Inc.
885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Care)
215-442-6260 (SDS)
www.crcindustries.com
Made in U.S.A.
15A

