

#2095-99B



WARNING: Contains Heptane 142-82-5, Dimethyl-polysiloxane 63148-62-9. Harmful or fatal if swallowed. Progressively higher exposure to vapor may cause irritation to eyes and respiratory tract, headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. Product is extremely flammable and should be kept from all flames and other ignition sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Vapors are heavier than air and can collect in low areas. **FIRST AID:** In case of eye and skin contact, flush with water for 15 minutes. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician. **DISPOSAL:** Unused contents and containers must be disposed of in accordance with all federal, state and local regulations. Empty containers may be offered to a qualified recycler. Do not dump into any body of water. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

To view M.S.D.S.: Tear (DO NOT CUT) label by running a fingernail down between perforations, removing this tab. Fold back label. Do not remove until can is empty.

DIRECTIONS: Read entire label before using this product.

1. Spray silicone in light, even coats to areas requiring lubrication or moisture protection.
2. Repeat step 1 until adequate lubrication or protection is achieved.
3. Re-apply Silicone as needed to maintain performance.
4. Do not apply while equipment is energized.

SPECIAL USAGE WARNINGS: • Contents extremely flammable. • Do not smoke while spraying. • Extinguish all flames, pilot lights, and heaters. • Do not apply while equipment is energized. • Vapors will accumulate readily and may ignite. • Use only with adequate ventilation; maintain ventilation during use and until vapors are gone.



- LUBRICATES, WATERPROOFS and PROTECTS mechanical and electrical components.
- ODORLESS, COLORLESS, NON-STAINING FILM provides superior lubricity for metal and non-metal surfaces.
- HELPS PREVENT CORROSION to equipment located in wet or harsh environments.
- CLINGS FIRMLY to surfaces, minimizing excess run-off.
- WIDE TEMPERATURE RANGE of -40°F to +400°F.
- MEETS FDA REGULATION CFR 21-178.3570 (lubricant, incidental food contact).
- AUTHORIZED BY USDA for use in federally inspected meat and poultry plants.
- MATERIAL SAFETY DATA SHEET printed on back of label for your convenience and safety. (The CRC MSDL™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827.)



99B
Made in U.S.A.
CRC#521B



ELECTRICAL GRADE

Silicone

Multi-Purpose Lubricant



**Lubricates, Waterproofs & Protects
Provides Thin, Clear Film
Food Grade Formula**

**No. 02095
Net Contents 15 fl. oz. (444 mL)**

**DANGER: EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.**

Read warnings on back panel.

©1999 CRC Industries, Inc., Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Service)
215-442-6260 (MSDS)
CRC#521B

Silicone
Part # 02095
99B
Net Wt. 15 fl. oz. (444 mL)
www.crcindustries.com
DANGER: EXTREMELY
FLAMMABLE. HARMFUL
OR FATAL IF SWALLOWED.