




Industrial

HF™ Contact Cleaner

■ HIGH-FLASHPOINT

■ Precision Cleaning Solvent

Part No. 02126



02126

NET WEIGHT 32 lbs (14.5 Kg)

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Do not store bulk container above 80°. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. FOR SPILLS, use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal. **DISPOSAL:** Used and unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. **EMPTY** containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimers. Do not dump into sewers, on the ground, or into any body of water.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately.

CAUTION: Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.

Use only in a well ventilated area. Use with adequate ventilation. Open doors and windows or other means to ensure fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave area. For additional information, consult the Material Safety Data Sheet for this product.

HEALTH	1	REACTIVITY	0
FLAMMABILITY	1	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

VOC Category: Electronic Cleaner VOC Limit: 75%

KEEP OUT OF REACH OF CHILDREN

WARNING: HARMFUL OR FATAL IF SWALLOWED. Read warnings carefully.

- High Flash Point 205° F
- Precision cleaning solvent instantly removes grease, oil, dirt and other contaminants
- High purity formula for reliability
- RoHS Compliant
- Zero VOC's
- NSF Registered #017401, Category Code: K2

WARNING: Contains Petroleum Distillate 64742-47-8.

©2006 CRC Industries, Inc.

Warmminster, PA 18974

800-521-3168 (Technical information)

800-272-4620 (Customer Service)

215-442-6260 (MSDS)

www.crcindustries.com

06A CRC#493A Made in U.S.A.

FOR CHEMICALS CALL CHEMTREC

1-800-424-9300



C

78254

02126

3