

ELECTRICAL GRADE



TM

CRC CABLE CLEAN® HF™ - "High Flash"

High Voltage Splice Cleaner

- Aggressively removes anti-oxidation compounds, silicones, adhesives and ground contaminants.
- Reduces arcing potential and current leakage at splice and termination junctions.
- Compatible with virtually all elastomeric and thermoplastic insulators, jackets and cable cores.
- Moderate evaporation rate and wiping action of lint-free cloth reduces amount of product necessary to thoroughly clean cables.
- Effective alternative to chlorinated, ozone depleting and terpene cleaners.

DIRECTIONS:

1. Shut-off or disconnect power supply and be sure all stored energy has been drained from the system.
2. For best results, use a mild abrasive before applying cable clean.
3. Apply liberally with lint-free cloth or use a spray applicator with an intermittent spray pattern to dislodge contaminants.
4. If necessary, repeat process until surface is clean.
5. Wipe with a dry lint-free cloth making sure all contaminants have been removed.
6. Allow product to fully evaporate and vent before insulating cables.
7. Do not apply while equipment is energized.

WARNING: Contains Petroleum Distillate 64742-48-9. Harmful or fatal if swallowed. Progressively higher exposure to vapor may cause irritation to eyes and respiratory tract, and other central nervous system effects. Product is combustible and should be kept from all flames and other ignition sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Vapors are heavier than air and can collect in low areas.

FIRST AID: In case of eye and skin contact flush with water for 15 minutes. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure call a physician immediately.

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Wash thoroughly after handling. Do not enter where observer is present and equipped with rescue gear. Vapors of this product may develop a flammable atmosphere in contact with flames, sparks or ignition sources. Do not cut or weld containers due to explosion hazard.

FOR SPILLS: Use proper protective equipment. Take precautions as necessary to prevent contamination of surface or ground water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills evacuate the area, dike and transfer into containers for disposal.

DISPOSAL: Unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. EMPTY containers may be offered to a licensed reconditioner. Unused contents may be offered to a licensed reclaimer. DO NOT DUMP IN SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

DO NOT USE ON SENSITIVE ELECTRONIC EQUIPMENT SUCH AS TAPE DECKS, VCRs, COMPUTERS, ETC. USE A CRC PRECISION CLEANER.

©1996 CRC Industries, Inc.

Warminster, PA 18974

96A CRC#493

Technical Service: 800-521-3168

Customer Service: 800-272-4620

Made in U.S.A.



CABLE CLEAN®

HF™

"High Flash"

High Voltage Splice Cleaner

Non-Chlorinated

Flash point above 142°F



Part No. 02171

Net Contents 1 pt. 14 fl. oz./30 fl. oz. (888mL)

DANGER: COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED.

Read warnings on back panel.