

CRC® Technical Grade 3-36®

DIRECTIONS: Read entire label before using this product.

1. Do not apply while equipment is energized. Allow to dry at least 4 to 6 hours before energizing. 2. Spray light, even coat to protect surfaces and to seal out moisture. 3. Apply liberally to loosen rusted parts. 4. Spray wet surfaces until run-off is clear and moisture free.

INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto.

1. No aplique el producto mientras el equipo esté conectado. Deje que se seque al menos entre 4 y 6 horas antes de conectar el equipo. 2. Rocíe una capa ligera y pareja para proteger las superficies y para que actúe como sellador contra la humedad. 3. Aplique generosamente para aflojar las piezas oxidadas. 4. Rocíe las superficies húmedas hasta que queden libres de excedentes y sin humedad.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

Precautionary Statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Contains Hydroretreated light distillates (64742-47-8), Light mineral oil (8042-47-5), n-Butyl stearate (123-95-5), Carbon dioxide (124-38-9), and Petrolatum (8009-03-8). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias.

Consejos de prudencia: Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes. **Primeros Auxilios:** En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. No provoque vómitos.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata conduce la electricidad. Mantenga fuera del alcance de todas las fuentes eléctricas vivas, incluso bornes de baterías, solenoides, tableros eléctricos y otros componentes electrónicos. Pasar por alto esta advertencia puede derivar en lesiones graves provocadas por fuego explosivo y/o descarga eléctrica.

©2016 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974 Made in U.S.A. 16A, CRC# 591B/C
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS) www.crcindustries.com



Nonfood Compounds
Program Listed
Category Code: H2
Reg.# 017424



Technical Grade 3-36® Multi-Purpose Precision Lubricant

Lubricante Multi Propósito de Precisión

Lubricates & Protects All Metals
Displaces Moisture & Stops Corrosion

Lubrica y Protege Todos los Metales
Desplaza la Humedad y Detiene la Corrosión

DANGER: FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

PELIGRO: INFLAMABLE.
SU INGESTIÓN ES PERJUDICIAL
O MORTAL. CONTENIDO BAJO
PRESIÓN. MANTENGA FUERA
DEL ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.



No. 03003
Net Wt./Peso Neto
11 oz (312 g)

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: Technical Grade 3-36® Multi-Purpose Precision Lubricant
Product code 03003
Recommended use Multi-purpose lubricant
Restrictions None known.
Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974
Phone: 215-674-4300
Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)
Gases under pressure (Compressed gas)
Health hazards Aspiration hazard (Category 1)
Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
Hydrotreated light distillates	64742-47-8	60 – 70
Light mineral oil	8042-47-5	10 – 20
n-Butyl stearate	123-95-5	3 – 5
Carbon dioxide	124-38-9	1 – 3
Petrolatum	8009-03-8	1 – 3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.
Eye contact Rinse with water. Get medical attention if irritation develops and persists.
Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting.
Most important symptoms/effects Aspiration may cause pulmonary edema and pneumonitis.
Special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO₂).
Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.
Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Absorb in vermiculite, dry sand, earth or other absorbent material and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

7. Handling and storage

Handling Pressurized container. Do not pierce or burn, even after use. When using, do not eat, drink or smoke. Avoid breathing mist or vapor. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.
Storage Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Store in a well-ventilated place. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
Carbon dioxide	PEL	9000 mg/m ³
Light mineral oil	TWA	5 mg/m ³
Petrolatum	TWA	5 mg/m ³
n-Butyl stearate	TWA	10 mg/m ³
Hydrotreated light distillates	TWA	100 mg/m ³

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).
Skin protection Wear protective gloves such as neoprene or nitrile. Wear appropriate clothing to prevent skin contact.
Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Amber liquid.
Odor threshold Not available.
Melting point/freezing point -56 °F (-49 °C)
Flash point 200 °F (93 °C) Tag Closed Cup
Explosive limit - lower (%) 0.6
Vapor pressure 1558 hPa
Relative density 0.84
Partition coefficient (n-octanol/water) Not available.
Auto-ignition temperature 392 °F (200 °C)
Decomposition temperature Not available.
Viscosity Not available.
VOC (Weight %): 0%

10. Stability and reactivity

Reactivity Non-reactive
Possibility of hazardous reactions No
Conditions to avoid Heat, flames and sparks. Temperatures exceeding the flash point. Incompatible materials.
Incompatible materials Strong oxidizing agents.
Hazardous decomposition products Carbon oxides.

11. Toxicological information

Information on likely routes of exposure:
Ingestion May be fatal if swallowed and enters airways.
Inhalation Prolonged inhalation may be harmful.
Skin contact Prolonged skin contact may cause temporary irritation.
Eye contact Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics
Aspiration may cause pulmonary edema and pneumonitis.
Information on toxicological effects:
Acute toxicity May be fatal if swallowed and enters airways.
Respiratory sensitization Not a respiratory sensitizer.
Skin sensitization Not expected to cause skin sensitization.
Carcinogenicity Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.
Reproductive toxicity Not expected to cause reproductive or developmental effects.
Aspiration hazard May be fatal if swallowed and enters airways.
Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions The dispensed liquid product is not a RCRA hazardous waste. Empty container can be recycled.
Hazardous waste code Not regulated

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 None
See full SDS for additional information

16. Other information

Issue date 5/16/2016 **CRC #591B/C** **Version #** 03