

CRC® 3-36®

DIRECTIONS: Read entire label before using this product. 1. Do not apply while equipment is energized. 2. To lubricate and protect metal surfaces: Spray in light, even coats. 3. To free rusted parts: Apply liberally and allow to penetrate. 4. To displace moisture: Spray wet surfaces until run-off is clear and moisture-free.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause an allergic skin reaction.



Precautionary Statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.

Contains Hydrotreated light distillates (64742-47-8), Catalytic dewaxed paraffin oils (64742-70-7, 64742-71-8), Dipropylene glycol monomethyl ether acetate (88917-22-0), n-Butyl stearate (123-95-5), Carbon dioxide (124-38-9), Fatty acids dimers (61788-89-4), Petrolatum (8009-03-8), d-Limonene (5989-27-5) and Terpinolene (586-62-9). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

©2016 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974 CRC# 510F 16A
www.crcindustries.com Made in U.S.A.
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS)



3-36®

Multi-Purpose Lubricant & Corrosion Inhibitor

**Frees Rusted Parts
Stops Squeaks & Squeals
Lubricates & Protects All Metals
Displaces Moisture &
Stops Corrosion**



Nonfood Compounds
Program Listed
Category Code: H2
Reg.# 017411



Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

**DANGER: FLAMMABLE.
HARMFUL OR FATAL IF
SWALLOWED. MAY CAUSE AN
ALLERGIC SKIN REACTION.
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.**
Read warnings on back panel.

No. 03004
Net Wt.
5 oz (142 g)

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty.

Identification

3-36® Multi-Purpose Lubricant & Corrosion Inhibitor

Product code 03004

Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive,
Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

Issue date 4/13/2016

CRC# 510F Ver. #03

Ingredients

Chemical name	CAS number	TWA	%	SARA 313
Dihydroretard				
light distillates	64742-47-8	100 mg/m ³	60 – 70	No
Catalytic dewaxed heavy				
paraffin oils	64742-70-7	5 mg/m ³	10 – 20	No
Catalytic dewaxed light				
paraffin oils	64742-71-8	5 mg/m ³	5 – 10	No
Dipropylene glycol monomethyl				
ether acetate	88917-22-0	N/A	3 – 5	No
n-Butyl stearate	123-95-5	10 mg/m ³	3 – 5	No
Carbon dioxide	124-38-9	9000 mg/m ³	1 – 3	No
Petrolatum	8009-03-8	5 mg/m ³	1 – 3	No
Fatty acids dimers	61788-89-4	5 mg/m ³	< 1	No
d-Limonene	5989-27-5	165.5 mg/m ³	< 0.2	No
Terpinolene	586-62-9	N/A	< 0.2	No

Hazards

Health: Skin sensitization (Category 1)

Aspiration hazard (Category 1)

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Inhalation Prolonged inhalation may be harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Carcinogenicity Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Physical: Flammable aerosols (Category 1)

Gases under pressure (Compressed gas)

Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame. Do not pierce or burn, even after use. Keep away from heat, sparks and open flame.

First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. DO NOT induce vomiting.

Advice for doctor Provide general supportive measures and treat symptomatically.

Personal Protection

Eye/face Wear safety glasses with side shields (or goggles).

Skin Use protective gloves such as neoprene or nitrile. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

Safe Handling

General Pressurized container: Do not pierce or burn, even after use.

When using, do not eat, drink or smoke. Avoid breathing gas, mist or vapor. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Fire Use water fog, alcohol resistant foam, dry chemicals or carbon dioxide (CO₂). Firefighters must wear self-contained breathing apparatus and full protective clothing. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Spill clean-up Remove sources of ignition. Beware of the explosion danger. Ventilate the area. Wipe up with absorbent material (e.g. cloth, fleece). Avoid discharge into drains, water courses or onto the ground.

Storage Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Store in a well-ventilated place. Keep away from heat, sparks and open flame.

Disposal The dispensed liquid product is not a RCRA hazardous waste.

Transport UN1950, Aerosols, flammable, 2.1, limited quantity

Properties

Appearance Blue green liquid.

Odor Pleasant.

Melting point/freezing point -56 °F (-49 °C)

Initial boiling point 380 °F (193 °C)

Flash point 192 °F (89°C)

Explosive limit - lower (%) 0.6

Explosive limit - upper (%) 5.5

Evaporation rate Slow

Vapor pressure 1431 hPa

Vapor density > 1 (Air = 1)

Relative density 0.84

Solubility(ies) Negligible in water.

Auto-ignition temperature 428 °F (220 °C)

VOC (Weight %): 0%

Stability Stable

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Carbon oxides. Sulfur oxides. Hydrocarbons.