



3-36[®]

Multi-Purpose Lubricant & Corrosion Inhibitor

Cleans
Lubricates
Penetrates
Loosens Corrosion

Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

DANGER: HARMFUL OR FATAL IF SWALLOWED.
MAY CAUSE AN ALLERGIC SKIN REACTION.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.



Nonfood Compounds
Program Listed
Category Code: H2
Reg.# 017429



No. 03006

**Net Contents:
1 gal (3.78 L)**

CRC® 3-36® Multi-Purpose Lubricant & Corrosion Inhibitor

- LUBRICATES and PROTECTS moving parts and metal surfaces.
- PENETRATES and LOOSENS rusted parts and sticky mechanisms.
- CLEANS light soils and contaminants from non-plastic surfaces.
- DISPLACES MOISTURE from wet or flooded equipment.
- PREVENTS the return of moisture and corrosion by leaving a thin, protective film.

DIRECTIONS: *Read entire label before using this product.*

For best results, remove heavy contaminant from surface before using. Do not apply directly to electrical contacts, hot surfaces, open flames or ignition sources while equipment is energized. To Lubricate: Apply a thin even film where metals meet. Allow product to penetrate or thoroughly coat all surface areas. Re-apply as needed to maintain desired lubrication. **To Prevent Corrosion:** For use indoors or in protected outdoor areas up to 1 year. Apply an even coat over entire surface. Be sure to coat edges. Film penetrates cracks, crevices and pores to protect trouble spots. Increase film thickness in harsh or humid environments. Wipe lightly without removing film for a shiny, polished appearance. **To Remove Moisture:** Apply liberally using spray applicator or dipping method. Tilt object and apply product until run-off turns from white to clear amber in color. When dipping, agitate objects slowly to accelerate process. Allow power equipment to vent before restoring power.

Danger

Combustible liquid. May be fatal if swallowed and enters airways. May cause an allergic skin reaction.

Precautionary Statements

Keep away from flames and hot surfaces-No smoking. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing gas, mist or vapor. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eye protection/face protection. Wash thoroughly after handling. Keep cool. Do not store container above 100 °F/38 °C. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

First Aid

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.

Contains hydrotreated light distillates (64742-47-8), catalytic dewaxed paraffin oils (64742-70-7, 64742-71-8), dipropylene glycol monomethyl ether acetate (88917-22-0), n-butyl stearate (123-95-5), fatty acids dimers (61788-89-4), petrolatum (8009-03-8), d-limonene (5989-27-5) and terpinolene (586-62-9). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

©2016 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Care)
215-442-6260 (SDS)

Health: 1 Flammability: 2 Reactivity: 0 PPE: B

www.crcindustries.com
Made in U.S.A. 16A CRC# 510F

