

# CRC Gasket Remover

**DIRECTIONS:** Read entire label before using this product. 1. Do not apply while equipment is energized. 2. Wear eye protection and rubber gloves or other non-porous hand protection. Protect painted surfaces from overspray, as product will dissolve paint. 3. Gasket removal: spray liberal coating on gasket and adhesive and allow to set for 5-10 minutes. Remove with putty knife and dry rag. 4. Paint and graffiti removal: spray liberal coating on painted surface. Allow to dry and brush with a stiff bristle brush.

**INSTRUCCIONES:** Lea la etiqueta completa antes de usar este producto. 1. No aplique el producto mientras el equipo esté conectado. 2. Utilice protección para los ojos y guantes de goma u otro tipo de protección no porosa para manos. Proteja las superficies pintadas del exceso de rocío, dado que el producto disuelve la pintura. 3. Eliminator de juntas: rocíe una capa abundante sobre la junta y el adhesivo y deje actuar por 5-10 minutos. Retire con una espátula y un trapo seco. 4. Eliminator de pintura y grafitos: rocíe una capa abundante sobre la superficie pintada. Deje secar y limpie con un cepillo de cerdas dura.

**Danger:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child.



**Precautionary Statements:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container. Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing gas, mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

**First Aid:** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

Contains Acetone (67-64-1), Liquefied petroleum gas (68476-86-8), N-Methyl-2-pyrrolidone (672-50-4), Xylene (1330-20-7), and Ethylbenzene (100-41-4). This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

**Electrical Shock Hazard:** This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

**Peligro:** Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea. Provoca irritación ocular grave. Puede irritar las vías respiratorias. Puede provocar somnolencia o vértigo. Sospechable de dañar la fertilidad o dañar al feto.

**Consejos de prudencia:** Lea las instrucciones especiales antes de su uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantenga lejos de calor/spasmas/lamas al descubierto/superficies calientes. - No fumar. No rocíe sobre una llama abierta u otra fuente de ignición. No aplique el producto sobre un equipo conectado. Recipiente presurizado. No perforar ni quemar, aun después del uso. Apegue todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Evite la inhalación de neblina o vapor. Evite la inhalación de gases. Lávese cuidadosamente después de la manipulación. Use guantes/instrumentaria protectora/equipo de protección para los ojos la cara. Almacénelo en lugar bien ventilado. Guarde bajo llave. Proteja de la luz solar. No exponer a temperaturas superiores a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

**Primeros Auxilios:** En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. No provoque vómitos. En caso de contacto con la piel: Lavar con abundante agua. Si ocurre irritación de la piel, busque atención médica. Quitar la ropa contaminada y lavarla antes de volver a usarla. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGÍA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si persiste la irritación de los ojos, busque atención médica. En caso de exposición demostrada o sospecha, busque atención médica.

Este producto contiene componentes químicos que en el Estado de California se conoce como causantes de cáncer y defectos de nacimiento u otros daños reproductivos. Su mal uso deliberado, concentrando e inhalando su contenido es legal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

**Peligro de Descarga Eléctrica:** Esta lata conduce la electricidad. Mantenga fuera del alcance de todas las fuentes eléctricas vivas, incluso bornes de baterías, solenoides, tableros electrónicos y otros componentes electrónicos. Pasar por alto esta advertencia puede derivar en lesiones graves provocadas por fuego explosivo y/o descarga eléctrica.

VOC Category: Gasket Remover | VOC Limit: 50%

Made in U.S.A.

©2016 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974

16A CRC# 553B

800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS)

www.crcindustries.com



# Gasket Remover

## Remover de Junta

Removes Gaskets, Paint and Graffiti

Remueve Juntas, Pintura y Grafitos



Nonfood Compounds  
Program Listed  
Category Code: C3  
Reg.# 017394



**DANGER: FLAMMABLE.**  
HARMFUL OR FATAL IF SWALLOWED.  
CAUSES SKIN AND EYE IRRITATION.  
CONTENTS UNDER PRESSURE.  
KEEP AWAY FROM CHILDREN.  
Read warnings on back panel.

**PELIGRO: INFLAMABLE.**  
SU INGESTIÓN ES PERJUDICIAL  
O MORTAL. PROVOCA IRRITACIÓN  
CUTÁNEA Y OCULAR.  
CONTENIDO BAJO PRESIÓN.  
MANTENGA FUERA DEL  
ALCANCE DE LOS NIÑOS.  
Lea las advertencias en el dorso.



**No. 03017**  
**Net Wt./Peso Neto**  
**12 oz (340 g)**

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Resegue (NO CORTE) la etiqueta siguiendo estas perforaciones y dobléala hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

## 1. Identification

**Product identifier:** Gasket Remover  
**Product code:** 03017  
**Recommended use:** Gasket remover  
**Restrictions:** None known.  
**Manufactured or sold by:**  
CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974  
**Phone:** 215-674-4300  
**Emergency phone number:** CHEMTREC - 24 HOURS: 800-424-9300

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols (Category 1)  
Gases under pressure (Liquefied gas)

**Health hazards** Skin corrosion/irritation (Category 2)  
Serious eye damage/eye irritation (Category 2)  
Reproductive toxicity (Category 2 fertility)  
Specific target organ toxicity, single exposure (Category 3 respiratory tract irritation)  
Specific target organ toxicity, single exposure (Category 3 narcotic effects)  
Aspiration hazard (Category 1)

**Label elements (see front side of label)**

## 3. Composition/information on ingredients

### Hazardous components

Chemical name	CAS number	%
Acetone	67-64-1	50 – 60
Liquefied petroleum gas	68476-86-8	20 – 30
N-Methyl-2-pyrrolidone	872-50-4	10 – 20
Xylene	1330-20-7	1 – 3
Ethylbenzene	100-41-4	< 1

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

## 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.  
**Skin contact** Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice.  
**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.  
**Ingestion** Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.  
**Most important symptoms/effects** May cause drowsiness, dizziness, headache, nausea and vomiting. Skin and severe eye irritation. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis.  
**Special treatment needed** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## 5. Fire-fighting measures

**Suitable extinguishing media** Alcohol resistant foam. Water fog. Carbon dioxide (CO2). Dry chemical powder. Sand. Earth.  
**Unsuitable extinguishing media** None known.  
**Specific hazards** Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur.  
**Special protective equipment and precautions for firefighters** Firefighters must use standard protective equipment including flame resistant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA

## 6. Accidental release measures

**Personal precautions** Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them. Avoid breathing gas, mist or vapor.  
**Containment and cleaning up** Eliminate all ignition sources. Keep combustibles away from spilled material. Absorb in vermiculite, dry sand, earth or other absorbent material and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

## 7. Handling and storage

**Handling** Pressurized container: Do not pierce or burn, even after use. When using, do not eat, drink or smoke. Avoid breathing gas, mist or vapor. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.  
**Storage** Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Store in a well-ventilated place. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters.

## 8. Exposure controls/personal protection

### Occupational exposure limits

Components	Type	Value
Acetone	TWA	500 ppm
Ethylbenzene	TWA	20 ppm
Xylene	TWA	100 ppm
N-Methyl-2-pyrrolidone	TWA	10 ppm

**Appropriate engineering controls** Mechanical ventilation or local exhaust ventilation is recommended.

### Individual protection measures:

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection** Wear protective gloves such as butyl rubber. Wear appropriate clothing to prevent skin contact.

**Respiratory protection** If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

## 9. Physical and chemical properties

**Appearance** Light grey liquid.  
**Odor threshold** Not available.  
**Melting point/freezing point** -139 °F (-95 °C)  
**Flash point** 56 °F (13 °C) Tag Closed Cup  
**Explosive limit - lower (%)** 1  
**Vapor pressure** 1330 hPa  
**Relative density** 0.78  
**Solubility(ies)** Soluble.  
**Partition coefficient (n-octanol/water)** Not available.  
**Auto-ignition temperature** 473 °F (245 °C)  
**Decomposition temperature** Not available.  
**Viscosity** Not available.  
**VOC (Weight %):** 47.5% (2.9 lbs/gal, 351.5 g/l)

**Odor** Solvent.  
**pH** Not available.  
**Initial boiling point** 133 °F (56 °C)  
**Evaporation rate** Fast  
**Explosive limit - upper (%)** 12.8  
**Vapor density** > 1 (Air = 1)

## 10. Stability and reactivity

**Reactivity** Non-reactive  
**Chemical stability** Stable  
**Possibility of hazardous reactions** No  
**Conditions to avoid** Heat, flames and sparks. Incompatible materials.  
**Incompatible materials** Strong acids. Acids. Strong oxidizing agents. Halogens. Peroxides. Phenols.  
**Hazardous decomposition products** Carbon oxides.

## 11. Toxicological information

### Information on likely routes of exposure:

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.  
**Inhalation** May cause drowsiness, dizziness, headache, nausea and vomiting. May cause irritation to the respiratory system.  
**Skin contact** Causes skin irritation.  
**Eye contact** Causes serious eye irritation.  
**Symptoms related to the physical, chemical and toxicological characteristics** Skin irritation. Severe eye irritation. Irritation of nose and throat. Narcotic effects.  
**Information on toxicological effects:**  
**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.  
**Respiratory sensitization** Not available.  
**Skin sensitization** Not expected to cause skin sensitization.  
**Carcinogenicity** Suspected of causing cancer.  
**Reproductive toxicity** Suspected of damaging fertility or the unborn child.  
**Aspiration hazard** May be fatal if swallowed and enters airways.  
**Chronic effects** Prolonged exposure may cause chronic effects.

## 12. Ecological information

See full SDS for additional information

## 13. Disposal considerations

**Disposal instructions** This material must be disposed of as hazardous waste.  
**Hazardous waste code** D001: Waste Flammable liquid.

## 14. Transport information

**DOT shipping description:** UN1950, Aerosols, flammable, 2.1, limited quantity

## 15. Regulatory information

**SARA 313** Ethylbenzene, N-Methyl-2-pyrrolidone, Xylene  
See full SDS for additional information

## 16. Other information

Issue date 10/15/2014

CRC #553B

Version # 01