



Spray Adhesive Spray Adhesivo

Web Spray Pattern
Minimal Soak-In
High Tack Formula
Good Water Resistance

Patrón de rociado de web
Absorción mínima
Fórmula de alto poder de fijación
Buena resistencia al agua

Recommended for foam, foils, plastics, papers, cardboard, and cloths
Recomendado para poliestireno, papel metálico, plástico, papel, cartón y tela

DANGER: EXTREMELY FLAMMABLE. CAUSES SKIN AND EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

PELIGRO: EXTREMAMENTE INFLAMABLE. PROVOCA IRRITACIÓN CUTÁNEA Y OCULAR. PUEDE IRRITAR LAS VÍAS RESPIRATORIAS. CONTENIDO BAJO PRESIÓN. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.



No. 03018

1.01 lb / 16.25 oz (460 g)

DIRECTIONS: Read entire label before using this product. 1. Do not use on energized equipment. 2. Safe on most plastics. Test small area. 3. Shake well before using. 4. Always direct spray tip toward the surface to be bonded. 5. Hold can 6-12 inches from surface to be sprayed. 6. Apply a light uniform coat of adhesive to surface. 7. For POROUS substrates, apply two coats in opposite directions. 8. For PERMANENT bonds, apply a heavy coat to both surfaces, let dry for 3 to 5 minutes and press substrates together. 9. For NON-PERMANENT bonds, apply a light coating to one surface only, let dry for 5 minutes and bond. 10. After use, invert can and depress spray tip until spray is free of adhesive. 11. If clogged, clean with petroleum distillate.

INSTRUCCIONES: Lea la etiqueta completa antes de usar este producto. 1. No use este producto en equipos con corriente eléctrica. 2. Seguro en la mayoría de los plásticos. Comprobar en un área pequeña. 3. Agitar bien antes de usar. 4. Siempre direccione la punta de pulverización hacia la superficie a ser adherida. 5. Sujete la lata de 6 a 12 pulgadas de la superficie a pulverizarse. 6. Aplicar una capa ligera uniforme de adhesivo a la superficie. 7. Para sustratos POROSOS, aplicar dos capas en direcciones opuestas. 8. Para adherencias PERMANENTES, aplicar una capa gruesa a ambas superficies, secar durante 3 a 5 minutos y apretar los sustratos el uno contra el otro. 9. Para adherencias NO PERMANENTES, aplicar una capa ligera a solo una superficie, dejar secar durante 5 minutos y unir. 10. Después del uso, invierta la lata y libere la punta de pulverización hasta que el spray esté libre de adhesivo. 11. Si se tapa, limpiar con destilado de petróleo.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.



Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride, hydrogen chloride, and possibly phosgene. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

Contains acetone 67-64-1, n-hexane 110-54-3, propane 74-98-6, and n-chlorobenzotrifluoride 98-56-6. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Provoca irritación cutánea. Provoca irritación ocular grave. Puede irritar las vías respiratorias. Puede provocar somnolencia o vértigo. Susceptible de perjudicar la fertilidad. Puede provocar daños en los órganos tras exposiciones prolongadas o repetidas.

Consejos de Prudencia: Procurarse las instrucciones antes del uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada: mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. No respirar nieblas o vapores. Usar guantes/ropa de protección/equipo de protección para los ojos/la cara. Lávese cuidadosamente después de la manipulación. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. Al exponerlo al calor extremo o superficies calientes, los vapores pueden descomponerse en gases corrosivos y tóxicos como el fluoruro de hidrógeno, el cloruro de hidrógeno y, posiblemente, el fosgeno. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de contacto con la piel: Lavar con abundante agua. Si ocurre irritación de la piel: Busque atención médica. Quitar la ropa contaminada y lavarla antes de volverla a usar. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGIA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si persiste la irritación de los ojos: Busque atención médica. En caso de exposición demostrada o supuesta: Busque atención médica.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

©2016 CRC Industries, Inc., Warminster, PA 18974
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS) Made in U.S.A. 16A www.crcindustries.com

VOC Category: Web Spray Adhesive VOC Limit: 40%

WARNING: This product can expose you to benzene, which is known to the State of California to cause cancer, and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

ADVERTENCIA: Este producto puede exponerte a benceno que es conocido por el Estado de California para causar cáncer y defectos de nacimiento u otros daños reproductivos. Para obtener más información, vaya a www.P65Warnings.ca.gov.



S.D.[L.]
Safety Data Label



To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta, siguiendo estas perforaciones y dóblala hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

03018-16A LC29353000A

1. Identification

Product identifier: Spray Adhesive

Product code 03018

Recommended use General purpose aerosol adhesive

Restrictions None known.

Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)

Gases under pressure (Liquefied gas)

Health hazards Skin corrosion/irritation (Category 2)

Serious eye damage/eye irritation (Category 2A)

Reproductive toxicity (Category 2 fertility)

Specific target organ toxicity, single exposure

(Category 3 narcotic effects, respiratory tract irritation)

Specific target organ toxicity, repeated exposure (Category 2)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
acetone	67-64-1	30 – 40
propane	74-98-6	20 – 30
n-hexane	110-54-3	10 – 20
p-chlorobenzotrifluoride	98-56-6	5 – 10

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

Ingestion In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects Skin and eye irritation. May cause drowsiness, dizziness, headache, nausea and vomiting. May cause respiratory tract irritation.

Special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Water fog, Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards Extremely flammable aerosol. Pressurized container may rupture when exposed to heat or flame. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride, hydrogen chloride, and possibly phosgene.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them. Do not breathe gas, mist or vapor.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Absorb in vermiculite, dry sand, earth or other absorbent material and place into containers. Clean surface thoroughly to remove residual contamination. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Handling Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands after handling and before eating.

Storage Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place, away from incompatible materials.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
acetone	TWA	250 ppm
n-hexane	TWA	50 ppm
propane	PEL	1000 ppm

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields or goggles.

Skin protection Wear protective gloves such as neoprene. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Off-white liquid.

Odor Solvent.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -139 °F (-95 °C)

Initial boiling point 133 °F (56 °C)

Flash point -20 °F (-29 °C) Pensky-Martens Closed Cup

Evaporation rate 9.1 (BuAc = 1)

Explosive limit - lower (%) 0.9

Explosive limit - upper (%) 12.8

Vapor pressure 13.5 kPa

Vapor density 1.55 (Air = 1)

Relative density 0.72

Solubility(ies) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 437 °F (225 °C)

Decomposition temperature Not available.

Viscosity Not available.

VOC (Weight %):39.5% (2.4 lbs/gal, 284 g/l)

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Strong oxidizing agents. Acids.

Hazardous decomposition products Hydrogen fluoride. Hydrogen chloride. Phosgene.

11. Toxicological information

Information on likely routes of exposure:

Ingestion May cause central nervous system depression.

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness, dizziness, headache, nausea and vomiting. May cause irritation to the respiratory system.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Information on toxicological effects:

Acute toxicity Not classified.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity Not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity Suspected of damaging fertility.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions This material must be disposed of as hazardous waste.

Hazardous waste code D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 n-hexane

See full SDS for additional information

16. Other information

Issue date 1/3/2017

Version # 03