

Read entire label before
using this product.



Nonfood Compounds Program
Listed (H2) (#132080)


Knock'er Loose®

Penetrating Solvent

■ Dissolves Rust and Corrosion

■ Loosens Frozen Metal Parts

Part No. 03022



NET WEIGHT 35.5 lb (16.1 kg)



DANGER

Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.


PRECAUTIONARY STATEMENTS

Keep away from flames and hot surfaces-No smoking. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing gas, mist or vapor. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eye protection/face protection. Wash thoroughly after handling. Store in a well-ventilated place. Keep cool. Do not store container above 100 °F/38 °C. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

FIRST AID

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	1	REACTIVITY	0
FLAMMABILITY	2	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

Do not apply while equipment is energized.

- Quickly penetrates through rust and corrosion
- Rapidly frees corroded fasteners, pins and bound mechanisms
- Eases disassembly of mechanical equipment, fittings and fixtures

Contains petroleum distillates/naphtha (64742-46-7, 64742-47-8, 64742-48-9), dipropylene glycol monomethyl ether acetate (88917-22-0), turpentine oil (8006-64-2), 2,6-dimethyl-4-heptanone (108-83-8), pine oil (8002-09-3), and pinus sylvestris extract (94266-48-5).

©2016 CRC Industries, Inc.
885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Care)
215-442-6260 (SDS)
www.crcindustries.com
16A CRC#548A Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300

DATE
CODE:

