

CRC Water Based Silicone

NSF H1

DIRECTIONS: Read entire label before using this product.

1. Do not apply while equipment is energized.
2. Shake can before using.
3. Hold can 8" to 12" away from surface to be sprayed.
4. Use extension tube for pinpoint accuracy.

INSTRUCCIONES: Lea la etiqueta completa antes de usar este producto.

1. No aplicar con el equipo con corriente eléctrica.
2. Agitar la lata antes de usar.
3. Sujete la lata de 8" a 12" de distancia de la superficie a pulverizar.
4. Utilice un tubo prolongador para precisión.

Warning

Contains gas under pressure; may explode if heated.

Precautionary Statements

Observe good industrial hygiene practices. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49°C/120°F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause can to burst. Dispose of waste and residues in accordance with local authority requirements.

First Aid

Wash hands after handling.

Contains Water (7732-18-5), Liquefied Petroleum Gas (68476-86-8), White mineral oil (8042-47-5), Polydimethylsiloxane (63148-62-9), Ammonia (7664-41-7) and Sodium nitrite (7632-00-0). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard

This can will conduct electricity. Do not touch can to live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from electrical shock.

Advertencia

Contiene gas a presión; puede explotar si se calienta.

Consejos de Prudencia

Respete las normas para un manejo correcto de los químicos. No perforo ni incinere el envase. No exponer al calor ni almacenar a temperaturas superiores a 49°C/120°F. Usar con ventilación adecuada. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Proteger de la luz solar. Almacenar en un lugar bien ventilado. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminar los desperdicios y residuos de conformidad con la normativa promulgada por las autoridades locales.

Primeros Auxilios

Lávese las manos después del uso.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica

Este recipiente es conductor de electricidad. Mantenga la lata alejada de toda fuente eléctrica viva, incluyendo terminales de batería, solenoides, paneles eléctricos y otros componentes electrónicos. El no respetar estas advertencias puede causar heridas graves por descargas eléctricas.

©2014 CRC Industries, Inc., Warminster, PA 18974 Made in U.S.A. 14A CRC# 696A
800-521-3168 (Technical Information) • 800-272-4620 (Customer Service) • 215-442-6260 (SDS) www.crcindustries.com



Water Based Silicone

Silicona a Base de Agua

Non-Flammable • Lubricates & Protects
No inflamable • Lubrica y protege



Nonfood Compounds Program Listed
Category Code: H1 Reg.# 140129



WARNING:
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

ADVERTENCIA:
CONTENIDO BAJO PRESIÓN.
MANTENGA FUERA DEL
ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.

No. 03035
Net Wt./Peso Neto
13 oz. (369 g)

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label.
After viewing, reattach label. Do not completely remove label until can is empty.
Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegar la etiqueta.
No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: Water Based Silicone

Product code 03035

Recommended use Silicone-based multi-purpose lubricant

Restrictions None known.

Manufactured or sold by:

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Gases under pressure (Liquefied gas)

Health hazards Not classified.

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
Water	7732-18-5	70 – 80
Liquefied Petroleum Gas	68476-86-8	10 – 20
White mineral oil	8042-47-5	10 – 20
Ammonia	7664-41-7	< 0.2
Sodium nitrite	7632-00-0	< 0.2

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Skin contact Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Contact a physician or poison control center. Rinse mouth.

Do not induce vomiting without advice from poison control center.

Most important symptoms/effects Direct contact with eyes may cause temporary irritation.

Special treatment needed Provide general supportive measures and treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media Water, Foam, Dry chemicals, Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards Contents under pressure. Containers should be cooled with water to prevent vapor pressure build up. In the event of fire, cool tanks with water spray.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ensure adequate ventilation.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Handling Pressurized container. Do not pierce or burn, even after use. Wear appropriate protective equipment. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas.

Storage Store in a cool, dry place (below 120°F/49°C) and out of direct sunlight. Do not handle or store near an open flame, heat or other sources of ignition.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
Ammonia	TWA	25 ppm
White mineral oil	TWA	5 mg/m ³

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as butyl or neoprene.

Respiratory protection In case of inadequate ventilation, use respiratory protection.

9. Physical and chemical properties

Appearance Creamy white liquid.

Odor Mild mineral oil.

Odor threshold Not available.

pH 9.7

Melting point/freezing point 32 °F (0°C)

Initial boiling point 212 °F (100 °C)

Flash point None (Tag Closed Cup)

Evaporation rate Slow.

Explosive limit - lower (%) 16

Explosive limit - upper (%) 25

Vapor pressure 521 hPa

Vapor density Not available.

Relative density 0.94

Solubility(ies) Dispersible in water

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 500 °F (260 °C)

Decomposition temperature Not available.

Viscosity Not available.

VOC (Weight %): 10.1% (0.8 lbs/gal, 97.4 g/l)

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Sunlight. Extreme temperatures.

Incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Carbon, sulfur and nitrogen oxides. Silica. Formaldehyde.

11. Toxicological information

Information on likely routes of exposure:

Ingestion If swallowed, mild irritation to mouth, throat and other tissues of gastrointestinal system may result.

Inhalation Prolonged or excessive inhalation may cause respiratory tract irritation.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact Direct contact with eyes may cause temporary irritation.

Information on toxicological effects:

Acute toxicity Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory sensitization Not available.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

Reproductive toxicity Not expected to cause reproductive or developmental effects.

Aspiration hazard Based on available data, the classification criteria are not met.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions The dispensed liquid product is not a RCRA hazardous waste.

Empty container can be recycled.

Hazardous waste code Not regulated

14. Transport information

DOT shipping description: UN1950, Aerosols, non-flammable, 2.2, limited quantity

15. Regulatory information

SARA 313 None

See full SDS for additional information

16. Other information

Issue date 1/30/2014

CRC #696A

Version # 01