


Read entire label before
using this product.



Nonfood Compounds Program
Listed (H2) (#017387)

Industrial Chain & Wire Rope Lubricant

Extreme Duty Synthetic Lubricant with Moly



03052

Part No. 03052

NET WEIGHT 27.5 lbs (12.5 Kg)



DANGER

Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe mist or vapor. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

HEALTH	2*	REACTIVITY	0
FLAMMABILITY	3	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

FIRST AID

If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

Do not use on energized equipment. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Not for use in California.

- Contains no chlorinated solvents
- Synthetic lubricant fortified with moly for heavy duty chain and wire rope applications
- Low initial viscosity penetrates critical pin and bushing areas, then thickens to form a tenacious, long-lasting lubricant

Contains Hydrotreated light naphtha (64742-49-0), Acrylic copolymer (Proprietary), n-Hexane (110-54-3) and Neutral oils (72623-86-0, 8042-47-5).

©2013 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical information)
800-272-4620 (Customer Service)
215-442-6260 (SDS)
www.crcindustries.com

13A CRC#572B/E Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300

DATE
CODE:

