



Screwloose®

■ Penetrating Oil

Part No. 03063

■ Loosens Frozen Bolts

NET WEIGHT 31 lbs. (14 Kg)

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Storage of this container outside will cause label to become illegible. FOR SPILLS, use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal.

DISPOSAL: Used and unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. EMPTY containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. Do not dump into sewers, on the ground, or into any body of water.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately. CAUTION: Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.

Product is flammable keep from flames and other ignition sources. Do not apply while equipment is energized. Use only in a well ventilated area. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. Read warnings carefully.

- Quickly penetrates through rust and corrosion
- Rapidly frees corroded fasteners, pins and bound mechanisms
- Eases disassembly of mechanical equipment, fittings and fixtures
- Clear formula contains no dyes and leaves no mess.

WARNING: Contains Petroleum Distillates 8052-41-3 ,64742-47-8, Oleic Acid 112-80-1

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	1	REACTIVITY	0
FLAMMABILITY	2	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

©2003 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical information)
800-272-4620 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
03A CRC#575D Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300

