

CRC Food Grade Belt Dressing

NSF H1

DIRECTIONS: Read entire label before using this product.

1. For personal safety, do not apply while equipment is energized. 2. Spray a light, even coating on sides of belt in contact with pulleys. 3. Re-apply CRC Belt Dressing periodically to help extend belt and pulley bearing life. 4. Do not use on serpentine or positive drive belts (e.g. timing belts).

INSTRUCCIONES: Lea la etiqueta completa antes de usar este producto.

1. Para seguridad personal, no aplicar en equipos con corriente eléctrica. 2. Pulverice una capa ligera y uniforme en las laterales de la correa en contacto con las poleas. 3. Vuelva a aplicar el tratamiento para correas CRC periódicamente para ayudar a prolongar la vida de la correa y de los cojinetes de la polea. 4. No utilizar en serpentina o correas de tracción positiva (p. ej., correa de temporización).

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.



Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container. Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe gas, mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical attention.

Contains Hexane isomers (64742-49-0/107-83-5). Liquefied petroleum gas (68476-86-8). Isobutylene polymer (9003-29-6) and n-Hexane (110-54-3). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product. **Electrical Shock Hazard:** This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Puede provocar somnolencia o vértigo. Susceptible de perjudicar la fertilidad. Puede provocar daños en los órganos tras exposiciones prolongadas o repetidas.

Consejos de Precaución: Recabar instrucciones especiales antes de su uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener lejos de calor/chispas/lamas al descubierto/superficies calientes. - No fumar. No rocíe sobre una llama abierta u otra fuente de ignición. No aplique el producto sobre un equipo conectado. Reciente presurizado: No perforar ni quemar, aun después del uso. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. No respire gases, neblina o vapor. Usar guantes/instrumentaria protectora/equipo de protección para los ojos/la cara. Almacenar en lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a temperaturas superiores a 50°C/122°F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. No provoque vómitos. En caso de inhalación: Transportar a la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGÍA o a un médico si la persona se encuentra mal. En caso de exposición demostrada o sospecha: Busque atención médica.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Seguridad para este producto. **Peligro de Descarga Eléctrica:** Esta lata conduce la electricidad. Mantenga fuera del alcance de todas las fuentes eléctricas vivas, incluso bornes de baterías, solenoides, tableros eléctricos y otros componentes electrónicos. Pasar por alto esta advertencia puede derivar en lesiones graves provocadas por ruego explosivo y/o descarga eléctrica.

©2015 CRC Industries, Inc., Warminster, PA 18974 Made in U.S.A. 15A CRC# 439C/D
800-521-3168 (Technical Information) • 800-272-4620 (Customer Service) • 215-442-6260 (SDS) www.crcindustries.com



Food Grade Belt Dressing

Antideslizante para bandas, de grado sanitario



Nonfood Compounds Program Listed
Category Code: H1 Reg.# 017386



DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN. Read warnings on back panel.

PELIGRO: EXTREMAMENTE INFLAMABLE. SU INGESTIÓN ES PERJUDICIAL O MORTAL. CONTENIDO BAJO PRESIÓN. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS. Lea las advertencias en el dorso.

No. 03065
Net Wt./Peso Neto
10 oz. (284 g)

To review SDS: Tear (DO NOT CUT) label along these perforations and fold back label.
After viewing, reattach label. Do not completely remove label until can is empty.
Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegarla a la etiqueta.
No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: Food Grade Belt Dressing

Product code: 03065

Recommended use: Belt dressing

Restrictions: None known.

Manufactured or sold by:

CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number: CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)
Gases under pressure (Liquefied gas)

Health hazards Reproductive toxicity (Category 2 fertility)
Specific target organ toxicity, single exposure (Category 3 narcotic effects)
Specific target organ toxicity, repeated exposure (Category 2)
Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
Hydrotreated light naphtha	64742-49-0	60 – 70
Liquefied petroleum gas	68476-86-8	20 – 30
2-Methylpentane	107-83-5	10 – 20
Isobutylene polymer	9003-29-6	5 – 10
n-Hexane	110-54-3	1 – 3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with plenty of water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects: Vapors have a narcotic effect and may cause headache, fatigue, dizziness, drowsiness and nausea.

Special treatment needed: Provide general supportive measures and treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media: Water spray. Water fog. Foam. Dry chemical powder. Carbon dioxide. Sand. Earth.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards: Extremely flammable aerosol. Pressurized container may explode when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Material will float and may ignite on surface of water.

Special protective equipment and precautions for firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions: Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them.

Containment and cleaning up: Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Handling: Pressurized container. Do not pierce or burn, even after use. When using, do not eat, drink or smoke. Do not breathe gas, mist or vapor. Avoid contact with skin and eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage: Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Store in a well-ventilated place. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
n-Hexane	TWA	50 ppm
2-Methylpentane	TWA	500 ppm

Appropriate engineering controls: Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin protection: Wear protective gloves such as nitrile, PVC or Viton®. Wear appropriate clothing to prevent skin contact.

Respiratory protection: Wear positive pressure self-contained breathing apparatus (SCBA).

9. Physical and chemical properties

Appearance: Light amber liquid.

Odor: Mild solvent.

Odor threshold: Not available.

pH: Not available.

Melting point/freezing point: -245 °F (-154 °C)

Initial boiling point: 118 °F (48 °C)

Flash point: < 0 °F (< -17.8 °C) Tag Closed Cup

Evaporation rate: Fast

Explosive limit - lower (%): 1

Explosive limit - upper (%): 8

Vapor pressure: 1682 hPa

Vapor density > 1 (Air = 1)

Relative density: 0.64

Solubility(ies): Negligible in water.

Partition coefficient (n-octanol/water): Not available.

Auto-ignition temperature: 489 °F (254 °C)

Decomposition temperature: Not available.

Viscosity: Not available.

VOC (Weight %): 92.8% (5.2 lbs/gal, 626.3 g/l)

10. Stability and reactivity

Reactivity: Non-reactive

Chemical stability: Stable

Possibility of hazardous reactions: No

Conditions to avoid: Heat, flames and sparks. Incompatible materials.

Incompatible materials: Strong oxidizing agents. Chlorine.

Hazardous decomposition products: Carbon oxides.

11. Toxicological information

Information on likely routes of exposure:

Ingestion: May be fatal if swallowed and enters airways.

Inhalation: Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause damage to organs by inhalation.

Skin contact: Prolonged skin contact may cause temporary irritation.

Eye contact: Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects:

Acute toxicity: May be fatal if swallowed and enters airways. Narcotic effects.

Respiratory sensitization: Not available.

Skin sensitization: Not expected to cause skin sensitization.

Carcinogenicity: Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

Reproductive toxicity: Suspected of damaging fertility.

Aspiration hazard: May be fatal if swallowed and enters airways.

Chronic effects: May cause damage to organs through prolonged or repeated exposure.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions: This material must be disposed of as hazardous waste.

Hazardous waste code: D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 n-hexane

See full SDS for additional information

16. Other information

Issue date 2/12/2014

CRC #439C/D

Version # 01