

DIRECTIONS: Read entire label before using this product. 1. For personal safety, do not apply while equipment is energized. 2. Use Layout Fluid Remover in a well ventilated area. For best results, container should be used and stored at room temperature. 3. Hold can upright and depress actuator holding can 8-10 inches from surface to be cleaned. 4. Spray Layout Fluid Remover evenly across surface to be cleaned. 5. Wipe surface off with a clean cloth. **INSTRUCCIONES: Lea la etiqueta completa antes de usar este producto.** 1. Para seguridad personal, no aplicar en equipos con corriente eléctrica. 2. Use el Removedor de líquidos de layout en un área bien ventilada. Para mejores resultados, se debe utilizar y almacenar el recipiente a temperatura ambiente. 3. Sujete la lata en posición vertical y oprima el accionador sujetando la lata de 8 a 10 pulgadas del artículo a limpiarse. 4. Pulverice el Removedor de líquidos de layout uniformemente sobre la superficie a limpiarse. 5. Limpie la superficie con un paño limpio.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Toxic if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. Causes damage to organs (eyes). May cause damage to organs (liver, kidneys, brain, lungs) through prolonged or repeated exposure.

Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container. Do not pierce or burn, even after use. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe gas, mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/clothing/eye protection. Store in a well ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/ container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin or eye irritation occurs: Get medical attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical attention.

DANGER: POISON. Cannot be made nonpoisonous. Contains Acetone (67-64-1), Toluene (108-88-3), Carbon dioxide (124-38-9) and Methanol (67-56-1). This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Tóxico en caso de ingestión. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea. Provoca irritación ocular grave. Puede provocar somnolencia o vértigo. Susceptible de dañar al feto. Provoca daños en los órganos (ojos). Puede provocar daños en los órganos (hígado, riñones, cerebro, pulmones) tras exposiciones prolongadas o repetidas.

Consejos de Prudencia: Recabar instrucciones especiales antes de su uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener lejos de calor/chispas/llamas al descubrirlo/superficies calientes. - No fumar. No rocíe sobre una llama abierta u otra fuente de ignición. No aplique el producto sobre un equipo conectado. Recipiente presurizado: No perforar ni quemar, aun después del uso. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. No respire gases. No respire neblina o vapor. Lávese cuidadosamente después de la manipulación. No comer, beber o fumar al manipular el producto. Usar cuantes/ropa / la protección ocular. Almacenar en lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a temperaturas superiores a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. Enjuáguese la boca. No provoque vómitos. En caso de contacto con la piel: Lavar con abundante agua. Quitar la ropa contaminada y lavarla antes de volver a usarla. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y atenderse con facilidad. Proseguir con el lavado. Si ocurre irritación de la piel o los ojos: Busque atención médica. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. En caso de exposición demostrada o sospecha: Busque atención médica.

Este producto contiene un componente químico que en el Estado de California se conoce como una causa de cáncer y defectos de nacimiento u otros daños reproductivos. Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata conduce la electricidad. Mantenga fuera del alcance de todas las fuentes eléctricas vivas, incluso bornes de baterías, solenoides, tableros eléctricos y otros componentes electrónicos. Pasar por alto esta advertencia puede derivar en lesiones graves provocadas por fuego explosivo y/o descarga eléctrica.

©2015 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974 Made in U.S.A. 15B CRC# 594M
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS) www.crcindustries.com



Layout Fluid Remover

Removedor de Medios Superficiales

Super Strength Formula
Leaves No Residue, Non-Chlorinated

Fórmula súper potente
No deja residuos, No clorado



DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE BLINDNESS IF SWALLOWED. VAPOR HARMFUL. CAUSES SKIN AND EYE IRRITATION. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN. Read warnings on back panel.

PELIGRO: EXTREMAMENTE INFLAMABLE. SU INGESTIÓN ES PERJUDICIAL O MORTAL. PUEDE PROVOCAR CEGUERA SI ES TRAGADO. VAPOR DAÑINO. PROVOCA IRRITACIÓN CUTÁNEA Y OCULAR. CONTENIDO BAJO PRESIÓN. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS. Lea las advertencias en el dorso.



No. 03069
Net Wt./Peso Neto
12 oz (340 g)

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Resegue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblala hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: Layout Fluid Remover

Product code: 03069

Recommended use: Layout fluid remover

Restrictions: None known.

Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number: CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards: Flammable aerosols (Category 1)

Gases under pressure (Compressed gas)

Acute toxicity, oral (Category 3)

Skin corrosion/irritation (Category 2)

Serious eye damage/eye irritation (Category 2)

Reproductive toxicity (Category 2 the unborn child)

Specific target organ toxicity, single exposure (Category 1)

Specific target organ toxicity, single exposure (Category 3 narcotic effects)

Specific target organ toxicity, repeated exposure (Category 2)

Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

| Chemical name | CAS number | % |
|----------------|------------|---------|
| Acetone | 67-64-1 | 40 – 50 |
| Toluene | 108-88-3 | 20 – 30 |
| Carbon dioxide | 124-38-9 | 10 – 20 |
| Methanol | 67-56-1 | 10 – 20 |

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact: Remove contaminated clothing. Rinse skin with water. If skin irritation occurs: Get medical attention. Wash contaminated clothing before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance.

Most important symptoms/effects: May cause drowsiness, dizziness, headache, nausea and vomiting. Irritation of nose and throat. Severe eye irritation. Aspiration may cause pulmonary edema and pneumonitis. May cause blindness if swallowed.

Special treatment needed: Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media: Alcohol resistant foam. Water fog. Carbon dioxide (CO₂). Dry chemical powder. Sand. Earth.

Unsuitable extinguishing media: None known.

Specific hazards: Extremely flammable aerosol. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions: Remove all possible sources of ignition in the surrounding area. Do not breathe gas, mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Containment and cleaning up: Eliminate all ignition sources. Keep combustibles away from spilled material. Absorb in vermiculite, dry sand, earth or other absorbent material and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Handling: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not breathe gas, mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage: Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

| Components | Type | Value |
|----------------|------|----------|
| Acetone | TWA | 500 ppm |
| Carbon dioxide | TWA | 5000 ppm |
| Methanol | TWA | 200 ppm |
| Toluene | TWA | 20 ppm |

Appropriate engineering controls: Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin protection: Wear protective gloves such as neoprene, butyl rubber, Viton® and PVA. Wear appropriate clothing to prevent skin contact.

Respiratory protection: If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance: Clear liquid.

Odor threshold: Not available.

Melting point/freezing point: -144 °F (-98 °C)

Flash point < 0 °F (< -18 °C): Tag Closed Cup

Explosive limit - lower (%): 1.2

Vapor pressure: 5942 hPa

Relative density: 0.88

Partition coefficient (n-octanol/water): Not available.

Auto-ignition temperature: 725 °F (385 °C)

Decomposition temperature: Not available.

VOC (Weight %): 43.2% (2.9 lbs/gal, 350.6 g/l)

Odor: Solvent.

pH: Not available.

Initial boiling point: 133 °F (56 °C)

Evaporation rate: Fast.

Explosive limit - upper (%): 36

Vapor density > 1 (Air = 1):

Solubility(ies): Slightly soluble.

Viscosity: Not available.

10. Stability and reactivity

Reactivity: Non-reactive

Chemical stability: Stable

Possibility of hazardous reactions: No

Conditions to avoid: Heat, flames and sparks. Incompatible materials.

Incompatible materials: Acids, Aldehydes, Alkalies, Amines, Ammonia, Halogens, Peroxides.

Reducing agents: Strong oxidizing agents. Aluminum. Magnesium. Strong acids. Strong bases. Zinc.

Hazardous decomposition products: Carbon oxides. Formaldehyde.

11. Toxicological information

Information on likely routes of exposure:

Ingestion: Toxic if swallowed. May cause blindness if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Inhalation: May cause damage to organs by inhalation. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact: Causes skin irritation.

Eye contact: Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics: Aspiration hazard. Narcotic effects. Skin irritation. Severe eye irritation. Swallowing may cause blindness.

Information on toxicological effects:

Acute toxicity: May be fatal if swallowed and enters airways. Narcotic effects.

Respiratory sensitization: Not available.

Skin sensitization: Not expected to cause skin sensitization.

Carcinogenicity: Not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity: Suspected of damaging the unborn child.

Aspiration hazard: May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.

Chronic effects: May cause damage to organs (liver, kidneys, brain, lungs) through prolonged or repeated exposure.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions: This material must be disposed of as hazardous waste.

Hazardous waste code: D001: Waste Flammable liquid; F003 & F005: Waste Non-Halogenated Solvent

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1(6.1), limited quantity

15. Regulatory information

SARA 313 Methanol, Toluene

See full SDS for additional information

16. Other information

Issue date 12/18/2014

CRC #594M

Version # 01