

DIRECTIONS: Read entire label before using this product. 1. Do not apply while equipment is energized. 2. Shake well before use. 3. Spray upper edges of overlapping chain side plates and allow lubricant to set up before energizing.

INSTRUCCIONES: Lea la etiqueta completa antes de usar este producto. 1. No aplique el producto mientras el equipo está conectado. 2. Agite bien antes de usar. 3. Rocíe el extremo superior de las placas laterales de la cadena que se superponen y permita que el lubricante actúe antes de conectar el equipo.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility.



Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell, if in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

Contains 2-methylpentane 107-83-5, liquefied petroleum gas 68476-86-8, hydrotreated light naphtha 64742-49-0, petrolatum 8009-03-8, n-hexane 110-54-3, lubricating oils 72624-86-0, and white mineral oil 8042-47-5. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea. Provoca irritación ocular. Puede provocar somnolencia o vértigo. Susceptible de perjudicar la fertilidad.

Consejos de prudencia: Procurarse las instrucciones antes del uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener alejado del calor/de chispas/de llamas al descubierto/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierto o cualquier otra fuente de ignición. Recipiente a presión: No perforar ni quemar, incluso después del uso. No aplique el producto sobre un equipo conectado. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Evitar respirar nieblas o vapores. Usar guantes/ropa de protección/equipo de protección para los ojos/la cara. Lávese cuidadosamente después de la manipulación. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. NO provocar el vómito. En caso de contacto con la piel: Lavar con abundante agua. En caso de irritación cutánea: Consultar a un médico. Quitar la ropa contaminada y lavarla antes de volverla a usar. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGÍA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si la irritación ocular persiste, consultar a un médico. En caso de exposición demostrada o supuesta: consultar a un médico.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata de metal puede conducir la electricidad. Manténgala alejada de todas las fuentes eléctricas vivas. El incumplimiento de esta advertencia puede resultar lesiones graves y/o incendio repentino.

Not for use in California.

©2016 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS) www.crcindustries.com



TAC 2[®]

Adhesive Chain Lubricant

Lubricante de Cadena Adhesiva

Reduces Friction and Wear
Resists Water Wash Off

Reduce la Fricción y el Desgaste
Resiste la Limpieza con Agua

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CAUSES SKIN AND EYE IRRITATION. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN. Read warnings on back panel.

PELIGRO: EXTREMAMENTE INFLAMABLE. SU INGESTIÓN ES PERJUDICIAL O MORTAL. PROVOCA IRRITACIÓN CUTÁNEA Y OCULAR. CONTENIDO BAJO PRESIÓN. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS. Lea las advertencias en el dorso.

No. 03076
Net Wt./Peso Neto
10 oz (283 g)



Nonfood Compounds
Product List# H2
Reg.# 144243



To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Resegue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblala hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: TAC 2® Adhesive Chain Lubricant

Product code: 03076

Recommended use: Industrial chain lubricant

Restrictions: None known.

Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number: CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)
Gases under pressure (Liquefied gas)
Health hazards Skin corrosion/irritation (Category 2)
Serious eye damage/eye irritation (Category 2B)
Reproductive toxicity (Category 2 fertility)
Specific target organ toxicity, single exposure (Category 3 narcotic effects)
Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
2-methylpentane	107-83-5	30 – 40
liquefied petroleum gas	68476-86-8	20 – 30
hydrotrated light naphtha	64742-49-0	10 – 20
petrolatum	8009-03-8	5 – 10
n-hexane	110-54-3	3 – 5
lubricating oils	72623-86-0	1 – 3
white mineral oil	8042-47-5	1 – 3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Rinse skin with water/shower. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects: Aspiration may cause pulmonary edema and pneumonitis. Vapors have a narcotic effect and may cause headache, fatigue, drowsiness, dizziness, and nausea. Skin and eye irritation.

Special treatment needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media: Water fog, Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards: Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions: Keep unnecessary personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them.

Containment and cleaning up: Eliminate all ignition sources. Keep combustibles away from spilled material. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Prevent entry into waterways, sewer, basements or confined areas.

7. Handling and storage

Handling: Pressurized container. Do not pierce or burn, even after use. When using, do not eat, drink or smoke. Avoid breathing mist or vapor. Avoid contact with skin and eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage: Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Store in a well-ventilated place. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
hydrotrated light naphtha	PEL	100 ppm
n-hexane	TWA	50 ppm
petrolatum	TWA	5 mg/m ³
white mineral oil	TWA	5 mg/m ³
2-methylpentane	TWA	500 ppm
lubricating oils	TWA	5 mg/m ³

Appropriate engineering controls: Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin protection: Wear protective gloves such as nitrile, neoprene, and viton/butyl. Wear appropriate clothing to prevent skin contact.

Respiratory protection: If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance: Blue viscous liquid.

Odor threshold: Not available.

Melting point/freezing point: < -76 °F (< -60 °C)

Flash point: < 0 °F (< -17.8 °C) Tag Closed Cup

Explosive limit - lower (%): 1.0

Vapor pressure: 1529 hPa

Relative density: 0.71

Partition coefficient (n-octanol/water): Not available.

Auto-ignition temperature: 437 °F (225 °C)

Decomposition temperature: Not available.

Viscosity: Not available.

VOC (Weight %): 81.3% (4.8 lbs/gal, 577 g/l)

Odor: Mild petroleum.

pH: Not available.

Initial boiling point: 118 °F (48 °C)

Evaporation rate: Fast

Explosive limit - upper (%): 8.0

Vapor density: > 1 (Air = 1)

Solubility(ies): Negligible in water.

10. Stability and reactivity

Reactivity: Non-reactive

Possibility of hazardous reactions: No

Conditions to avoid: Heat, flames and sparks. Incompatible materials.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: None known.

Chemical stability: Stable

11. Toxicological information

Information on likely routes of exposure:

Ingestion: Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Inhalation: Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Skin contact: Causes skin irritation.

Eye contact: Causes eye irritation.

Symptoms related to the physical, chemical, and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. Vapors have a narcotic effect and may cause headache, fatigue, drowsiness, dizziness, and nausea. Skin and eye irritation.

Information on toxicological effects:

Acute toxicity: May be fatal if swallowed and enters airways.

Respiratory sensitization: Not a respiratory sensitizer.

Skin sensitization: Not expected to cause skin sensitization.

Carcinogenicity: Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

Reproductive toxicity: Suspected of damaging fertility.

Aspiration hazard: May be fatal if swallowed and enters airways.

Chronic effects: Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions: If discarded, this product is considered a RCRA ignitable waste, D001.

Hazardous waste code: D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 n-hexane

See full SDS for additional information

16. Other information

Issue date 1/24/2017

CRC #932A/B

Version # 03