



Industrial Food Grade Penetrating Oil

H1 Rated

Use on Food Processing Equipment

Odorless, Tasteless, Colorless

Frees Rusted Parts

No. 03087

Net Contents 1 gal. (3.78L)

DANGER: HARMFUL OR FATAL IF SWALLOWED.

Read warnings on back panel.



Food Grade Penetrating Oil

- EXCELLENT PENETRATION and lubricating properties for food processing equipment.
- QUICKLY penetrates and dissolves rust, gum and corrosion.
- WILL NOT HARM paint, plastic or wood surfaces.
- FREES RUSTED PARTS.
- NON-SILICONE FORMULA.
- NSF H1 Registered #130545 for use in meat and poultry plants.

Directions: Read entire label before using this product.

1. Liberally apply directly on corroded fasteners.
2. Allow oil to seep between joints and surface area.
3. Tap joints lightly to aid process.
4. Loosen or remove fastener.
5. If necessary, repeat steps 1-3 until fastener breaks free.
6. Severely frozen or welded fasteners may require the help of a power tool or nut cracker to loosen.
7. Do not apply while equipment is energized.

WARNING: Contains Petroleum Distillate 64742-47-8, White Mineral Oil 8042-47-5. Harmful or fatal if swallowed. Progressively higher exposure to vapor can cause irritation to eyes and respiratory tract, headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. Product should be kept from all flames and other ignition sources. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Vapors are heavier than air and can collect in low areas.

FIRST AID:

In case of eye or skin contact, flush with water for 15 minutes. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately.

HANDLING AND SPILL PRECAUTIONS:

Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentrations unless air supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Vapors of this product may develop a flammable atmosphere in contact with flames, sparks, or ignition sources. Do not cut or weld containers due to explosion hazard. FOR SPILLS, use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small

spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal.

DISPOSAL:

Unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. EMPTY containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. DO NOT DUMP IN SEWERS, ON THE GROUND OR INTO ANY BODY OF WATER.

For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

©2003 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
Made in U.S.A. CRC#5558 03A

