

DIRECTIONS: Read entire label before using this product. 1. Do not apply while equipment is energized. 2. For best performance, use on a clean surface. 3. Shake well before use. 4. Hold can 8" to 12" away from surface to be sprayed. 5. Spray with a light, even film. 6. Wipe off excess with a clean cloth. 7. Repeat application if necessary.

INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto. 1. No aplique el producto mientras el equipo esté conectado. 2. Para obtener el mejor rendimiento, aplíquelo sobre una superficie limpia. 3. Agite bien antes de usar. 4. Mantenga la lata alejada, a una distancia de entre 8" y 12" de la superficie a rociar. 5. Rocíe con una capa ligera y pareja. 6. Quite el excedente con un paño limpio. 7. Repita la aplicación si fuera necesario.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.



Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container. Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Disposal of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

Contains Branched, cyclic and linear and heptane (426260-76-6), Isopropyl alcohol (67-63-0), n-Butane (106-97-8), n-Heptane (142-82-5), Propane (74-98-6) and Toluene (108-88-3). **WARNING:** This product contains chemicals known to the State of California to cause birth defects or other reproductive harm. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea. Provoca irritación ocular grave. Puede irritar las vías respiratorias. Puede provocar somnolencia o vértigo. Susceptible de dañar al feto. Puede provocar daños en los órganos tras exposiciones prolongadas o repetidas.

Consejos de Prudencia: Procurarse las instrucciones antes del uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener alejado del calor/de chispas/de llamas al descubierta/de superficies calientes. - No fumar. No vaporizar sobre una llama al descubierta o cualquier otra fuente de ignición. No aplique el producto sobre un equipo conectado. Recipiente a presión: No perforar ni quemar, incluso después del uso. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se está secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. No respirar nieblas o vapores. Lávese cuidadosamente después de la manipulación. Usar guantes/ropa de protección/equipo de protección para los ojos/la cara. Almacenar en un lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a una temperatura superior a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. NO provocar el vómito. En caso de contacto con la piel: Lavar con abundante agua. Si ocurre irritación de la piel: Busque atención médica. Quitar la ropa contaminada y lavarla antes de volverla a usar. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGIA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si persiste la irritación de los ojos: Busque atención médica. En caso de exposición demostrada o supuesta: Busque atención médica.

ADVERTENCIA: Este producto contiene un componente químico que en el Estado de California se conoce como una causa de defectos de nacimiento u otros daños reproductivos. Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata conduce la electricidad. Mantenga fuera del alcance de todas las fuentes eléctricas vivas, incluso bombas de baterías, solenoides, tableros eléctricos y otros componentes electrónicos. Pasar por alto esta advertencia puede derivar en lesiones graves provocadas por fuego explosivo y/o descarga eléctrica.

©2015 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974 Made in U.S.A. 15A
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS) www.crcindustries.com



Dry Graphite Lube

Lubricante Seco de Grafito

Effective up to 850°F Constant
Excellent Conductivity
Dries Rapidly at Room Temperature

Efectivo hasta una temperatura
constante de 850 ° F
Excelente Conductividad
Seca Rápidamente a Temperatura
Ambiente

DANGER: EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
CAUSES SKIN AND EYE IRRITATION.
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

PELIGRO: EXTREMAMENTE
INFLAMABLE. SU INGESTIÓN ES
PERJUDICIAL O MORTAL. PROVOCA
IRRITACIÓN CUTÁNEA Y OCULAR.
CONTENIDO BAJO PRESIÓN.
MANTENGA FUERA DEL
ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.



No. 03094

Net Wt./Peso Neto
10 oz (284 g)



To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: Dry Graphite Lube
Product code 03094
Recommended use Dry film lubricant
Restrictions None known.
Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974
Phone: 215-674-4300
Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)
Gases under pressure (Liquefied gas)
Health hazards Skin corrosion/irritation (Category 2)
Serious eye damage/eye irritation (Category 2)
Reproductive toxicity (Category 2 the unborn child)
Specific target organ toxicity, single exposure (Category 3 respiratory tract irritation, narcotic effects)
Specific target organ toxicity, repeated exposure (Category 2)
Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
Branched, cyclic and linear heptane	426260-76-6	30 – 40
Isopropyl alcohol	67-63-0	20 – 30
n-Butane	106-97-8	10 – 20
n-Heptane	142-82-5	10 – 20
Propane	74-98-6	10 – 20
Toluene	108-88-3	1 – 3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects May cause drowsiness, dizziness, headache, nausea and vomiting. Skin and eye irritation. Aspiration may cause pulmonary edema and pneumonitis.

Special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media None known.

Specific hazards Extremely flammable aerosol. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Absorb in vermiculite, dry sand, earth or other absorbent material and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

7. Handling and storage

Handling Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not breathe gas, mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
Isopropyl alcohol	TWA	200 ppm
n-Butane	STEL	1000 ppm
Propane	PEL	1000 ppm
Toluene	TWA	20 ppm

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as neoprene or nitrile. Wear appropriate clothing to prevent skin contact.

Respiratory protection If needed, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Wear positive pressure self-contained breathing apparatus (SCBA) in case of emergency.

9. Physical and chemical properties

Appearance Black liquid.

Odor threshold Not available.

Melting point/freezing point -139 °F (-95 °C)

Flash point -20 °F (-29 °C) Pensky-Martens Closed Cup

Explosive limit - lower (%) 1

Vapor pressure 1835 hPa

Relative density 0.66

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 750 °F (399 °C)

Decomposition temperature Not available.

VOC (Weight %): 97.9% (5.4 lbs/gal, 646.2 g/l)

Odor Solvent.

pH Not available.

Initial boiling point 181 °F (83 °C)

Evaporation rate Moderate

Explosive limit - upper (%) 12.7

Vapor density 1.55 (Air = 1)

Solubility(ies) Not available.

Viscosity Not available.

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine.

Hazardous decomposition products Carbon oxides.

11. Toxicological information

Information on likely routes of exposure:

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration hazard. Narcotic effects. Skin, eye and respiratory tract irritation.

Information on toxicological effects:

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.

Respiratory sensitization Not available.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

Reproductive toxicity Suspected of damaging the unborn child.

Aspiration hazard May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions This material must be disposed of as hazardous waste.

Hazardous waste code D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity, MARINE POLLUTANT

15. Regulatory information

SARA 313 Toluene

See full SDS for additional information

16. Other information

Issue date 6/23/2015

Version # 01