

WARNING: Contains Water 7732-18-5, Polydimethylsiloxane 63148-62-9, Isoparaffinic hydrocarbon 64742-48-9, Coconut diethanolamide 68603-42-9 and Hydrocarbon propellant 68476-86-8. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause mild to moderate eye irritation, mild skin irritation, irritation to upper respiratory tract, or headache. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying, if you experience any symptoms listed on this label, increase ventilation or leave the area. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call physician immediately. For additional information, consult MSDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do NOT dump in sewers, floor drains, on the ground or into any body of water.

KEEP AWAY FROM CHILDREN

To view Emergency M.S.D.S.: Tear (DO NOT CUT) label by running fingernail between perforations. Fold back label. Do not remove until can is empty.

- Colorless, odorless, non-staining film
- Reduces galling and friction
- Perfect for use on metal to non-metal contact areas
- Harmless to rubbers and plastics
- Material Safety Data Sheet printed on back of label for your convenience and safety (The CRC MSDJ™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827)

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from electrical shock.



08A
Made in U.S.A.
CRC#445B



DIRECTIONS: Read entire label before using this product.

1. Do not apply while equipment is energized.
2. Hold can 8" to 12" away from surface to be sprayed.
3. Spray a light, even film. Only use the necessary amount to achieve results.
4. Wipe off excess with cloth.
5. Repeat application when necessary.



Industrial

Slick Surface Silicone

Lubricant

**Reduces Friction
Non-Flammable
Low VOC Formula
Plastic Safe**



**No. 03105
Net Wt. 18 oz. (510 g)**

**WARNING: MAY CAUSE EYE IRRITATION.
CONTENTS UNDER PRESSURE.**
Read warnings on back panel.



©2008 CRC Industries, Inc., Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Service)
215-442-6260 (MSDS)
CRC#445B

Slick Surface Silicone
Part # 03105 08A
Net Wt. 18 oz. (510 g)
www.crcindustries.com
Made in U.S.A.

**WARNING: MAY CAUSE EYE IRRITATION.
CONTENTS UNDER PRESSURE.**

**M.S.D.[L].™**Material Safety Data Label from CRC
U.S. Patent Number 5,056,827**SLICK SURFACE SILICONE**

MANUFACTURED BY: CRC INDUSTRIES, INC.

885 LOUIS DRIVE, WARMINSTER, PA 18974

PHONE: (215) 674-4300

PRODUCT - 03105

24 HOUR EMERGENCY INFORMATION - CALL CHEMTREC 1-800-424-9300**1 HAZARDOUS INGREDIENT INFORMATION**

CAS #	ACGH	OSHA	%SARA	OTHER	313
Water	7732-18-5	NE	NE	NE	7080 NO
Polydimethylsiloxane	63148-62-9	NE	NE	NE	38 NO
Synthetic isoparaffinic hydrocarbon	64742-48-9	NE	NE	NE	1-5 NO
Coconut diethanolamide	68403-42-9	NE	NE	NE	1-5 NO
Liquefied petroleum gas	68476-86-8	1000ppm	1000ppm	NE	1020 NO

2 CHEMICAL AND PHYSICAL PROPERTIES

Appearance and Odor: White emulsion, lemon odor
 Specific Gravity: .99
 Boiling Point: ~212°F
 Freezing Point: ND
 Vapor Pressure: ND
 Evaporation Rate: <1 (ether=1)
 Vapor Density: ND (air=1)
 pH: 9.8
 Solubility: Soluble in water
 VOC Content: 17.1%
 g/L: 169.3 lbs./gal.: 1.41

3 FIRE AND EXPLOSION DATA

Flashpoint: None
 Flammable Limits:
 Extinguishing Media: not needed
 Unusual Hazards:
 Method: TCC
 UEL: ND

4 REACTIVITY AND STABILITY

Stability: Stable
 Hazardous Decomposition products: None
 Conditions to avoid: Keep away from heat and direct sunlight. Do not touch container to live electrical sources. Container will conduct electricity. Dropping of containers may cause bursting.
 Materials to avoid: Strong oxidizers, strong acids.

5 PROTECTION INFORMATION

Ventilation: Use adequate ventilation to prevent the accumulation of vapors.
 Respiratory: Use a self-contained breathing apparatus in confined spaces and for emergencies.
 Gloves: Rubber or Nitrile.
 Eye & Face: Safety goggles

6 POTENTIAL HEALTH EFFECTS

1. Acute Overexposure: EYE: May cause eye irritation. SKIN: Prolonged exposure may cause mild irritation. INHALATION: Prolonged exposure may cause a headache or irritation to the throat. INGESTION: Ingestion of large amounts may cause stomach ache and irritation of the gastrointestinal tract.

2. Chronic Overexposure: None identified.
Medical Conditions Generally Aggravated by Exposure: Eye and skin conditions.

Chemical Listed as Carcinogen or Potential Carcinogen
 OSHA: No IARC Monographs: No NTP: No

7 EMERGENCY AND FIRST AID MEASURES

(if symptoms persist, call a physician)

Inhalation: Remove to fresh air. Give artificial respiration if necessary.

Eyes: Flush with large amounts of water for 15 minutes.

Skin: Remove contaminated clothing and wash area with soap and water

Ingestion: Give victim 1-2 glasses of water. Call a physician.

8 ACCIDENTAL RELEASE MEASURES

Precautions to be taken in Handling and Storage: Store in a cool, dry area. Aerosols may explode when heated above 120°F. Be sure to use this product with adequate ventilation.

Steps to be taken in case material is released or spilled: Usually not a problem with aerosols. Areas should be ventilated. Absorbent should be used to pick up excess material.

Waste Disposal: All used and unused product should be disposed of in conformance with local, state and federal regulations.

9 NFPA/HMIS HAZARD RATINGS

Health: 1 Flammability: 1 Reactivity: 0 PPE: B

10 ADDITIONAL INFORMATION

Prepared By: Michelle Rudnick Date: 7/15/08

CRC # 445B

Technical Information: (800) 521-3168

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

NA=Not Applicable

Abstract Service

NE=Not Established

LEL=Lower Exposure Limit

g/L=grams per liter

lbs./gal.=pounds per gallon

ND=Not Determined

PPM=Parts Per Million

TCC=Tag Closed Cup

UEL=Upper Exposure Limit

PPE=Personal Protection Equipment

RO=Reportable Quantity

CAS=Chemical