

**WARNING:** Contains Isobutane 107-83-5, n-Hexane 110-54-3, Methanol 67-58-1 and Petroleum Distillate 64742-48-9. Product is extremely flammable. Do not use on energized equipment. Continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to the vapor may cause irritation to eyes, respiratory tract, headaches, dizziness, drowsiness, anesthesia, unconsciousness and other central nervous system effects. Vapors are heavier than air and can collect in low areas. **FIRST AID:** In case of eye and skin contact, flush with water for 15 minutes. If swallowed, may be harmful or fatal. Do NOT induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately. **DISPOSAL:** Unused contents and containers must be disposed of in accordance with all federal, state and local regulations. Empty containers may be offered to a qualified recycler. Unused contents may be offered to a licensed reclaimer. **DO NOT DUMP IN SEWERS, ON THE GROUND OR INTO ANY BODY OF WATER.** For additional information, consult the Material Safety Data Sheet for this product.

**KEEP AWAY FROM CHILDREN**

To view M.S.D.S.: Tear (DO NOT CUT) label by running a fingernail down between perforations, removing this tab. Fold back label. Do not remove until can is empty.

**Directions: Read entire label before using this product.**

1. Shut off power supply. Be sure all stored power is drained from system and allow hot surfaces to cool before using product.
2. For optimum results, prepare heavily soiled or corroded surfaces by buffing with a mild abrasive.
3. When ready to use, puncture the top of the can as indicated on the cap; insert the supplied trigger sprayer into the can.
4. Tilt surface and spray until clean.
5. Allow excess cleaner to run off.
6. Allow product to dry completely and thoroughly vent system before restoring power.
7. For personal safety, do not apply while equipment is energized.

**SPECIAL USAGE WARNINGS:** Contents extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Use only with adequate ventilation. Maintain ventilation during use and until vapors are gone.

**ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Keep away from all live electrical sources including battery terminals, terminals, electrical panels and other electronic components. DO NOT use with ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

- **QUICK DRYING, HIGH PURITY FORMULA** evaporates rapidly and leaves no residue.
- **SAFE FOR USE** on most plastics and paper tapes.
- **INCREASES PERFORMANCE,** prolongs equipment life and prevents electrical failures by dissolving light oils, flux, dirt and fingerprints on contacts, relays, switches, circuits and PC boards.
- **MEETS USDA 1998** guidelines for use in meat and poultry plants.
- **MATERIAL SAFETY DATA SHEET** printed on back of label for your convenience and safety. (The CRC® MSDL™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827.)



00A  
Made in U.S.A.  
CRC#599C



Leaves No Residue  
Plastic Safe

# Contact Cleaner

Quick Drying Formula

Industrial **QD**™



DANGER, EXTREMELY FLAMMABLE,  
HARMFUL OR FATAL IF SWALLOWED.

QD™ Contact Cleaner  
Net Contents 15 fl. oz. (444 mL)  
Part # 03133 00A  
www.crcindustries.com

©2000 CRC Industries, Inc., Warminster, PA 18974  
800-272-4620 (Customer Service)  
215-442-6260 (MSDS)  
CRC#599C

No. 03133  
Net Contents 15 fl. oz. (444 mL)

**DANGER: EXTREMELY FLAMMABLE. HARMFUL  
OR FATAL IF SWALLOWED.**

Read warnings on back panel.