

CRC Contact Cleaner 2000®

DIRECTIONS: Read entire label before using this product. 1. For personal safety, do not apply while equipment is energized. 2. May be harmful to some plastics. Do not use on polycarbonate plastics, such as Lexan®, if in doubt call the manufacturer of the equipment. Do not use on sensitive electronic equipment such as DVD's, computers, fax machines, copiers, printers, shredders, etc. 3. Spray until clean and allow to run off. Use extension tube for pinpoint cleaning. 4. Use an abrasive on surfaces with heavy carbon deposits or corrosion - remove residue with intermittent spray before reactivating system. 5. Product may collect and pool in unseen areas. Use a combustible gas detector to be certain there are no flammable vapors remaining before reactivation. 6. Periodic planned maintenance prolongs life expectancy of components and helps eliminate deposits that cause leakage. Use resistance measurements to determine frequency of application.

INSTRUCCIONES: Lea la etiqueta completa antes de usar este producto. 1. Para seguridad personal, no aplicar en equipos con corriente eléctrica. 2. Puede ser dañino para algunos plásticos. No usar en plásticos de policarbonato, tales como Lexan®, si tiene dudas, llame al fabricante del equipo. No utilizar en equipos electrónicos sensibles, tales como DVD's, computadoras, máquinas de fax, copadoras, impresoras, trituradoras de papel, etc. 3. Pulvisque hasta que el artículo esté limpio y deje separ. Utilice un tubo prolongador para limpieza detallada. 4. Utilice un abrasivo en superficies con depósitos grandes de carbono o corrosión - remueva los residuos con pulverización intermitente antes de reactivar el sistema. 5. El producto puede juntarse y acumularse en áreas que no estén a la vista. Use un detector de gas combustible para asegurar que no queden vapores inflamables antes de la reactivación. 6. El mantenimiento programado periódico prolonga la vida útil de los componentes y ayuda a eliminar depósitos que puedan causar pérdidas. Utilice mediciones de resistencia para determinar la frecuencia de la aplicación.

Danger: Flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness.



Precautionary Statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an

open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Use with adequate ventilation. Open doors and windows or other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing gas, mist or vapor. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride, hydrogen chloride and possibly phosgene. Do not eat, drink or smoke when using this product. Wear protective gloves and eye/face protection. Wash hands thoroughly after handling. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Rinse mouth. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Contents: CO2 (401 (Proprietary), Carbon dioxide (124-38-9), Decafluoropropane (138495-42-8) and Methanol (67-56-1). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Peligro: Aerosol inflamable. Contiene gas a presión; puede explotar si se calienta. Nocivo en caso de ingestión. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación ocular grave. Puede provocar somnolencia o vértigo.

Consejos de prudencia: Mantenga lejos de calor/chispas/llamas al descubierto/superficies calientes. - No fumar. No rocíe sobre una llama abierta u otra fuente de ignición. Recipiente presurizado. No perforar ni quemar, aun después del uso. Usar con ventilación adecuada. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. No respirar gas, niebla o vapor. Al exponer al calor extremo, los vapores pueden descomponerse en gases corrosivos y tóxicos como el fluoruro de hidrógeno, cloruro de hidrógeno y, posiblemente, el fosgeno. No comer, beber o fumar al manipular el producto. Usar cuantos de protección y equipo para proteger los ojos/la cara. Lavarse las manos cuidadosamente después de la manipulación. Almacenar en lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a temperaturas superiores a 50°C/122°F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. No provoque vómitos. Enjuáguese la boca. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGÍA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si persiste la irritación de los ojos: Busque atención médica.

Si mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata conduce la electricidad. Manténgala fuera del alcance de todas las fuentes eléctricas vivas, incluso bombes de baterías, solenoides, tableros electrónicos y otros componentes electrónicos. Pasar por ahí está advertencia puede derivar en lesiones graves provocadas por fuego explosivo y/o descarga eléctrica.

VOC Category: Electronic Cleaner VOC Limit: 75%

Not for use in California.

©2014 CRC Industries, Inc., Warminster, PA 18974
800-521-3168 (Technical Information)

800-272-4620 (Customer Service) • 215-442-6260 (SDS)
Made in U.S.A. 14A CRC# 657B
www.crcindustries.com



Contact Cleaner 2000® Precision Cleaner Limpiador de Precisión



Nonfood Compounds
Program Listed
Category Code: K2
Reg.# 017391



No Flash Point
No Residue

Sin punto de inflamación
No deja residuo

**DANGER: HARMFUL OR
FATAL IF SWALLOWED.
CAUSES EYE IRRITATION.
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.**

**PELIGRO: SU INGESTIÓN
ES PERJUDICIAL O MORTAL.
PROVOCA IRRITACIÓN OCULAR.
CONTENIDO BAJO PRESIÓN.
MANTENGA FUERA DEL
ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.**



No. 03150
Net Wt./Peso Neto
13 oz. (369 g)

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: Contact Cleaner 2000® Precision Cleaner
Product code 03150
Recommended use Precision electronics cleaner
Restrictions None known.
Manufactured or sold by:
CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974
Phone: 215-674-4300
Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 2)
Gases under pressure (Compressed gas)

Health hazards Acute toxicity, oral (Category 4)
Serious eye damage/eye irritation (Category 2A)
Specific target organ toxicity, single exposure (Category 3 narcotic effects)
Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components	CAS number	%
Chemical name		
C0z0l® 401	Proprietary	80 – 90
Carbon dioxide	124-38-9	5 – 10
Decafluoropentane	138495-42-8	5 – 10
Methanol	67-56-1	< 0.2

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air. Give artificial respiration if necessary. Do NOT give epinephrine (adrenaline). Call a POISON CENTER or doctor/physician.

Skin contact Rinse skin with water/shower. Get medical attention if irritation develops and persists. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. If victim is fully conscious, give 2 glasses of water.

Most important symptoms/effects Stinging, tearing, redness, swelling, and blurred vision. Narcotic effects.

Special treatment needed Treat symptomatically. Catecholamine drugs such as adrenaline should be used with special caution. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Powder. Water. Water spray. Foam. Carbon dioxide (CO₂).

Unsuitable extinguishing media None known.

Specific hazards Pressurized container may explode when exposed to heat or flame. Vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride, hydrogen chloride and possibly phosgene.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Containment and cleaning up Eliminate all ignition sources. Keep combustibles away from spilled material. Wipe up with absorbent material. Prevent entry into waterways, sewer, basements or confined areas. Use appropriate containment to avoid environmental contamination. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Handling Pressurized container. Do not pierce or burn, even after use. Do not taste or swallow. Avoid breathing gas, mist or vapor. Avoid contact with skin and eyes. Avoid prolonged exposure. Use only in well-ventilated areas. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains.

Storage Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
Carbon dioxide	TWA	5000 ppm
Methanol	TWA	200 ppm
Trans-1,2-dichloroethylene	TWA	200 ppm

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Use protective gloves such as nitrile, neoprene, PVA, or Viton®. Wear appropriate clothing to prevent skin contact.

Respiratory protection Wear positive pressure self-contained breathing apparatus (SCBA).

9. Physical and chemical properties

Appearance Clear colorless liquid.

Odor Slight ethereal.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -112 °F (-80 °C)

Initial boiling point 104 °F (40 °C)

Flash point None (Tag Closed Cup)

Evaporation rate Fast.

Explosive limit - lower (%) 2

Explosive limit - upper (%) 19.9

Vapor pressure 3308 hPa

Vapor density > 1 (Air = 1)

Relative density 1.27

Solubility(ies) Slight in water

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 860 °F (460 °C)

Decomposition temperature Not available.

Viscosity Not available.

VOC (Weight %): 57.5% (6.0 lbs/gal, 723.1 g/l)

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Incompatible materials.

Incompatible materials Strong oxidizing agents. Strong bases. Strong acids. Alkali or alkaline earth metals.

Hazardous decomposition products Carbon oxides. Carbonyl halides. Hydrogen fluoride. Hydrogen chloride. Phosgene. Formaldehyde.

11. Toxicological information

Information on likely routes of exposure:

Ingestion Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Skin contact Skin contact may cause temporary irritation.

Eye contact Causes serious eye irritation.

Information on toxicological effects:

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects. Eye irritation.

Respiratory sensitization Not available.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

Reproductive toxicity Not expected to be hazardous by OSHA criteria.

Aspiration hazard If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions The dispensed liquid product is not a RCRA hazardous waste. Empty container can be recycled.

Hazardous waste code Not regulated.

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 None
See full SDS for additional information

16. Other information

Issue date 2/4/2014 **CRC #657B** **Version #** 01