

CRC Ultra-Lite 3-36®

DIRECTIONS: Read entire label before using this product. 1. Do not apply while equipment is energized. 2. Spray in light, even coats to lubricate and protect metal surfaces. 3. Apply liberally and allow to penetrate minute openings and free corroded parts. 4. To displace moisture: Spray wet surfaces until run-off is clear and moisture-free.

INSTRUCCIONES: Lea la etiqueta completa antes de usar este producto. 1. No aplique el producto mientras el equipo esté conectado. 2. Rocíe en capas finas y parejas para lubricar y proteger superficies metálicas. 3. Aplique el producto en cantidad abundante y permita que penetre en las pequeñas aberturas y piezas corroídas. 4. Para quitar la humedad, rocíe las superficies hasta que desaparezca el excedente y no quede humedad.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.



Precautionary Statements: Keep away from heat/

sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing gas, mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

Contains Hydrotreated light distillates (6474-47-8), Corrosion inhibitor blend (Proprietary), Carbon dioxide (124-38-9) and Vanilla fragrances (Proprietary). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea. Puede provocar una reacción cutánea alérgica. Puede provocar somnolencia o vértigo.

Consejos de prudencia: Mantener lejos de calor/chispas/lamas al descubierto/superficies calientes. - No fumar. No rocíe sobre una llama abierta u otra fuente de ignición. No aplique el producto sobre un equipo conectado. Recipiente presurizado: No perforar ni quemar, aun después del uso. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Evite la inhalación de gas, neblina o vapor. Lávese cuidadosamente después de la manipulación. La ropa de trabajo contaminada no debe salir del lugar de trabajo. Use guantes de protección. Almacenar en lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a temperaturas superiores a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. No provoque vómitos. En caso de contacto con la piel: Lavar con abundante agua. En caso de irritación cutánea: Consultar a un médico. Quitar la ropa contaminada y lavarla antes de volver a usarla. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGIA o a un médico si la persona se encuentra mal.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata conduce la electricidad. Mantenga fuera del alcance de todas las fuentes eléctricas vivas, incluso bornes de baterías, solenoides, tableros eléctricos y otros componentes electrónicos. Pasar por alto esta advertencia puede derivar en lesiones graves provocadas por fuego explosivo y/o descarga eléctrica.

©2015 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974 Made in U.S.A. 15A CRC# 559A
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS) www.crcindustries.com



Ultra-Lite 3-36®

**Dry Film Lubricant
Displaces Moisture
Prevents Corrosion
Resists Oil and Dirt Build-up**

**Lubricante de Película Seco
Desplaza la Humedad
Previene la Corrosión
Resiste la Acumulación de
Suciedad y Aceite**



Nonfood Compounds
Program Listed
Category Code: H2
Reg.# 017425



**DANGER: FLAMMABLE. HARMFUL
OR FATAL IF SWALLOWED. CAUSES
SKIN IRRITATION. CONTENTS UNDER
PRESSURE. KEEP AWAY FROM
CHILDREN.** Read warnings on back panel.

**PELIGRO: INFLAMABLE. SU
INGESTIÓN ES PERJUDICIAL O
MORTAL. PROVOCA IRRITACIÓN
CUTÁNEA. CONTENIDO BAJO
PRESIÓN. MANTENGA FUERA
DEL ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.**



No. 03160
Net Wt./Peso Neto
11 oz (312 g)

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: Ultra-Lite 3-36®

Product code: 03160

Recommended use: Dry film lubricant

Restrictions: None known.

Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number: CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols (Category 1)
Gases under pressure (Compressed gas)

Health hazards Skin corrosion/irritation (Category 2)
Skin sensitization (Category 1)
Specific target organ toxicity, single exposure (Category 3 narcotic effects)
Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
Hydrotreated light distillates	64742-47-8	80 – 90
Corrosion inhibitor blend	Proprietary	5 – 10
Carbon dioxide	124-38-9	1 – 3
Vanilla fragrances	Proprietary	< 0.3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact: Remove contaminated clothing. Wash off with soap and plenty of water. In case of eczema or other skin disorders: Seek medical attention.

Eye contact: Rinse with water. Get medical attention if irritation develops and persists.

Ingestion: Call a physician or poison control center immediately. Rinse mouth.

Do not induce vomiting.

Most important symptoms/effects: Irritant effects. Narcotic effects. Rash. Redness. Pain.

Special treatment needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media: Powder. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO₂).

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards: Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions: Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Ventilate closed spaces before entering them. Avoid breathing gas, mist or vapor.

Containment and cleaning up: Eliminate all ignition sources. Keep combustibles away from spilled material. Absorb in vermiculite, dry sand, earth or other absorbent material and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

7. Handling and storage

Handling: Pressurized container: Do not pierce or burn, even after use. When using, do not eat, drink or smoke. Avoid breathing gas, mist or vapor. Avoid contact with skin, eyes and clothing. Avoid prolonged or repeated exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

Storage: Store in a cool, dry place (below 122°F/50°C) and out of direct sunlight. Store in a well-ventilated place. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
Carbon dioxide	TWA	5000 ppm
Hydrotreated light distillates	TWA	100 mg/m ³

Appropriate engineering controls: Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin protection: Wear protective gloves such as neoprene or nitrile. Wear appropriate clothing to prevent skin contact.

Respiratory protection: Wear positive pressure self-contained breathing apparatus (SCBA).

9. Physical and chemical properties

Appearance: Amber liquid.

Odor: Petroleum.

Odor threshold: Not available.

pH: Not available.

Melting point/freezing point: -72 °F (-58 °C)

Initial boiling point: 360 °F (6182 °C)

Flash point: 172 °F (78 °C) Tag Closed Cup

Evaporation rate: Slow

Explosive limit - lower (%): 0.6

Explosive limit - upper (%): 5.5

Vapor pressure: 1628 hPa

Vapor density: > 1 (Air = 1)

Relative density: 0.82

Solubility(ies): Negligible in water.

Partition coefficient (n-octanol/water): Not available.

Auto-ignition temperature: 457 °F (236 °C)

Decomposition temperature: Not available.

Viscosity: Not available.

VOC (Weight %): 43.8% (2.9 lbs/gal, 351.3 g/l)

10. Stability and reactivity

Reactivity: Non-reactive

Chemical stability: Stable

Possibility of hazardous reactions: No

Conditions to avoid: Heat, flames and sparks. Temperatures exceeding the flash point. Incompatible materials.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Carbon and calcium oxides. Aldehydes.

11. Toxicological information

Information on likely routes of exposure:

Ingestion: May be fatal if swallowed and enters airways.

Inhalation: Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Eye contact: Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Diarrrhea, dermatitis, irritation, rash, redness, pain, allergic skin reaction, headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects:

Acute toxicity: May be fatal if swallowed and enters airways. Narcotic effects. May cause an allergic skin reaction.

Respiratory sensitization: Not available.

Skin sensitization: May cause an allergic skin reaction.

Carcinogenicity: Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

Reproductive toxicity: Not expected to cause reproductive or developmental effects.

Aspiration hazard: May be fatal if swallowed and enters airways.

Chronic effects: Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions: This material must be disposed of as hazardous waste.

Hazardous waste code: Not regulated.

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313: None

See full SDS for additional information

16. Other information

Issue date: 5/12/2014

CRC #559A

Version # 01