



Ultra-Lite 3-36[®]

**Dry Film Lubricant
Prevents Corrosion
Resists Oil and Dirt Build-Up**

Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

DANGER: HARMFUL OR FATAL IF SWALLOWED.
CAUSES SKIN IRRITATION.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.



Nonfood Compounds
Program Listed
Category Code: H2
Reg.# 136113



No. 03161
Net Contents:
1 gal. (3.78 L)

CRC® Ultra-Lite 3-36®

- Lubricates. Prevents Corrosion. Displaces Moisture.
- Provides exceptional short term lubrication for light to medium loads.
- Prevents existing corrosion and rust from spreading.
- Fast drying. Non staining.
- Provides added safety of a high, 172° F flash point.
- Meets requirements of MIL-PRF-16173E, Grade 3.

DIRECTIONS: *Read entire label before using this product.*

For best results, remove heavy contaminant from surface before using. Do not apply directly to electrical contacts, hot surfaces, open flames, or ignition sources while equipment is energized.

To Lubricate: Apply a thin even film where metals meet. Allow product to penetrate or thoroughly coat all surface areas. Re-apply as needed to maintain desired lubrication.

To Prevent Corrosion: For use indoors or in protected outdoor areas up to 1 year. Apply an even coat over entire surface. Be sure to coat edges. Film penetrates cracks, crevices, and pores to protect trouble spots. Increase film thickness in harsh or humid environments. Wipe lightly without removing film for a shiny, polished appearance.

To Remove Moisture: Apply liberally using spray applicator or dipping method. Tilt object and apply product until run-off turns from white to clear amber in color. When dipping, agitate objects slowly to accelerate process. Allow power equipment to vent before restoring power.

Danger: Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.

Precautionary Statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eye protection/face protection. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

Contains Hydrotreated light distillates (64742-47-8) and Corrosion inhibitor blend (Proprietary). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

