

Read entire label before
using this product.




Nonfood Compounds Program
Listed (H2) (#136113)

Ultra-Lite 3-36[®]

■ Dry Film Lubricant

■ Prevents Corrosion



03163

Part No. 03163

NET WEIGHT 366 lbs. (166 kg)



DANGER

Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eye protection/face protection. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

FIRST AID

If swallowed: Immediately call a poison center/doctor.
Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

- Thin, non-staining dry film protects equipment and metal parts from corrosion for up to 9 months indoors
- Displaces moisture and water-based metal working compounds
- Dries within 30-90 minutes depending upon film thickness

Contains Hydrotreated light distillates (64742-47-8) and Corrosion Inhibitor blend (Proprietary).

©2014 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical information)
800-272-4620 (Customer Service)
215-442-6260 (SDS)
www.crcindustries.com
14A CRC#559A Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300

Batch No.:
Date Code:



0 78254 03163 7

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	1	REACTIVITY	0
FLAMMABILITY	2	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4