


Job 35956 95A Part 3170

**WARNING** Contains: 1,1-Dichloro-1-fluoroethane 1717-00-6, 1,1,1,2-Tetrafluoroethane 811-97-2, and Silicone fluid. Do not puncture, incinerate, or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in a well ventilated area. Avoid continuous breathing of vapors and spray mist. Avoid contact with skin or eyes. Overexposure to vapor may cause irritation to eyes and respiratory tract, dizziness and loss of concentration, central nervous system depression & irregular heartbeats (cardiac arrhythmias). Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Vapors displace oxygen available for breathing and can cause asphyxiation. Vapors are heavier than air and can collect in low areas, pits, small rooms or other unventilated areas. If ventilation is not adequate, respiratory protection should be used. Death can occur without warning if too much is breathed. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed may be harmful or fatal. Do not induce vomiting. If too much is breathed remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately.

**KEEP AWAY FROM CHILDREN**

To review Emergency M.S.D.S.: Tear (DO NOT CUT) label along these two perforations and fold back label. Do not remove label until can is empty.



95A  
Made in U.S.A.  
CRC # 489A

ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

- Directions:**
- Low odor silicone fluid exhibits high stability with very little change in viscosity and flow
  - When dry, will not boil, flash or get up to 600°F.
  - Prolonged performance, lubrication and releases permit longer intervals between scrape and wipe without jeopardizing fibers.
  - Material Safety Data Sheet printed on back of label MSD[L]™ is a proprietary label removal system patented under US Patent No. 5,056,827)
1. Shake well before use.
  2. For vertical application; insert tube with long end into valve and short end do not use tube.
  3. Press firmly when inserting tube. Tube will seat tightly in valve.
  4. Hold can 10-12 inches from spinnerette and spray with a thin, light coat.
  5. Repeat application as necessary.
  6. Do not use on energized equipment.



# Industrial Spinnerette Lubricant

Heat Stable to 600°F  
Vertical/Horizontal Actuator  
Patented MSDS Label

No. 03170  
Net Wt. 14 oz. (397 g)

**WARNING: VAPOR HARMFUL. EYE IRRITANT. CONTENTS UNDER PRESSURE.**  
Read warnings on back panel.

©1995 CRC Industries Inc., Warminster, PA 18974  
800-521-3168 (Tech. Info.)  
800-272-4620 (Cust. Service)  
Spinnerette Lubricant  
Part # 03170  
Net Wt. 14 oz. (397 g)  
**WARNING: VAPOR HARMFUL. EYE IRRITANT. CONTENTS UNDER PRESSURE.**