

CRC Battery Cleaner

DIRECTIONS: Read entire label before using this product. 1. Shake can well. 2. Spray on battery surface, terminals and connectors. Do not spray into battery cells. 3. Allow Battery Cleaner to soak for 1-5 minutes. 4. Rinse with water and wipe dry with cloth or towel. 5. For heavy build-up on terminals and connectors, use wire brush. 6. If necessary, repeat steps 2 through 5 until surface meets desired cleanliness. 7. Protect clean terminals with CRC Battery Protector. (Part # 03175).

INSTRUCCIONES: Leer en su totalidad el contenido de la etiqueta antes de usar el producto.

1. Agitar bien el envase. 2. Rocíar sobre la superficie de la batería, sobre los bornes y los terminales de conexión. No rociar el producto adentro de las celdas de la batería. 3. Dejar actuar el limpiador de baterías durante un período de 1 a 5 minutos. 4. Enjuagar con agua y secar con un paño o una toalla. 5. Si hay mucha suciedad en los bornes y terminales de conexión, usar primero un cepillo de alambre para limpiar. 6. Si aún fuera necesario, repetir los pasos 2 a 5 para terminar de limpiar las superficies. 7. Aplicar Protector de Baterías CRC a las terminales limpiadas. (Parte # 03175).

Warning: Contains gas under pressure; may explode if heated.

Precautionary Statements: Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49°C/120°F. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Protect from sunlight. Store in a well-ventilated place. Exposure to high temperature may cause can to burst. Dispose of waste and residues in accordance with local authority requirements.

First Aid: Wash hands after handling.

Contains Water (7732-18-5), Liquefied Petroleum Gas (68476-86-8) and 2-Butoxyethanol (111-76-2). This product contains chemicals known to the State of California to cause cancer. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Do not touch can to live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from electrical shock.

Advertencia: Contiene gas a presión; puede explotar si se calienta.

Consejos de prudencia: No perforo ni incinere el envase. No exponer al calor ni almacenar a temperaturas superiores a 49°C/120°F. Usar con ventilación adecuada. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Proteger de la luz solar. Almacenar en un lugar bien ventilado. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminar los desperdicios y residuos de conformidad con la normativa promulgada por las autoridades locales.

Primeros Auxilios: Lávese las manos después del uso.

Este producto contiene componentes químico que en el Estado de California se conoce como una causa de cáncer. Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Este recipiente es conductor de electricidad. Mantenga la lata alejada de toda fuente eléctrica viva, incluyendo terminales de batería, solenoides, paneles eléctricos y otros componentes electrónicos. El no respetar estas advertencias puede causar heridas graves por descargas eléctricas.

©2015 CRC Industries, Inc., 885 Louis Dr., Warmminster, PA 18974
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS)

Made in U.S.A. 15A CRC# 530B
www.crcindustries.com



Battery Cleaner

Limpiador de Batería

Assures maximum battery current flow
Promotes longer battery life

Promueve la vida útil de la batería

WARNING:
CONTENTS UNDER PRESSURE
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

ADVERTENCIA:
CONTENIDO BAJO PRESIÓN.
MANTENGA FUERA DEL
ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.



No. 03176
Net Wt./Peso Neto
11 oz (312 g)

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty.

Identification

Battery Cleaner

Product code 03176

Manufactured by: CRC Industries, Inc., 885 Louis Drive,
Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS:
800-424-9300

Issue date 9/12/2013

CRC# 530B Ver. # 01

Ingredients

Chemical name	CAS number	TWA	%	SARA 313
Water	7732-18-5	None	80 - 90	No
Liquefied Petroleum Gas	68476-86-8	None	5 - 10	No
2-Butoxyethanol	111-76-2	20 ppm	1 - 3	No

Hazards

Health: Not Classified.

Ingestion Expected to be a low ingestion hazard.

Inhalation Prolonged inhalation may be harmful.

Skin contact 2-Butoxyethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged.

Eye contact Direct contact with eyes may cause temporary irritation.

Carcinogenicity Not considered to be a carcinogen by IARC, ACGH, NTP or OSHA.

Chronic effects Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

Physical: Gases under pressure (Compressed gas)

Contains gas under pressure; may explode if heated. Do not puncture or incinerate. Do not expose to heat or store at temperatures above 49 °C/120 °F.

First-aid measures

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a POISON CENTER or doctor/physician.

Advice for doctor Provide general supportive measures and treat symptomatically.

Personal Protection

Eye/face Wear safety glasses with side shields (or goggles).

Skin Use protective gloves such as nitrile. Wear appropriate clothing to prevent skin contact.

Respiratory protection Use respirator if ventilation is inadequate.

Safe Handling

General Pressurized container: Do not pierce or burn, even after use. Do not smoke and do not spray near any sources of ignition or energized equipment. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid contact with skin and eyes. Avoid prolonged exposure. Wash after handling.

Fire Water. Stop leak if safe to do so. Containers should be cooled with water to prevent vapor pressure build up.

Spill clean-up Remove sources of ignition. Ventilate the area. Absorb in vermiculite, dry sand or earth and place into containers. This product is miscible in water. Stop leak if you can do so without risk. Prevent entry into waterways, sewer, basements or confined areas.

Storage Store in a cool, dry place (below 120°F/49°C) and out of direct sunlight. Store away from incompatible materials.

Disposal The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Dispose of contents/container in accordance with local/regional/national/international regulations.

Transport UN1950, Aerosols, non-flammable, 2.2, limited quantity

Properties

Appearance Clear liquid.

Odor Odorless.

Melting point/freezing point -103 °F (-75 °C)

Initial boiling point 212 °F (100 °C)

Flash point None (Closed Cup)

Explosive limit - lower (%) 1.3 %

Explosive limit - upper (%) 10.6 %

Evaporation rate Slow

Vapor pressure 269 hPa

Vapor density > 1 (Air = 1)

Relative density 1.04

Solubility(ies) Soluble in water

Auto-ignition temperature 446 °F (230 °C)

VOC (Weight %): 7.9% (0.68 lbs/gal / 82.16 g/l)

Stability Stable

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Carbon oxides.