

**WARNING:** Contains Tetrahydroethylene 127-18-4 & Carbon Dioxide 124-38-9. Do not puncture, incinerate or store can above 120° F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Do not use this product near open flames, welding operations or excessive heat. Vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Overexposure to vapors may cause eye and skin irritation, headaches, nausea, dizziness, irritation to upper respiratory tract and irregular heartbeats. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, protection should be used. For severe overexposure, call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product.

**KEEP AWAY FROM CHILDREN**

To review Emergency M.S.D.S.: Tear (DO NOT CUT) label along these two perforations and fold back label. Do not remove label until can is empty.

**Directions: Read entire label before using this product.**

1. Remove mechanical plates, covers, etc. to expose equipment interior. For best results, remove heavy deposits of contaminants by scraping with a wire brush.
  2. Protect all rubber parts, plastic parts and painted surfaces from overspray. Do not spray directly on painted surfaces.
  3. Spray until clean. Use extension tube for hard to reach areas.
  4. Air dry or wipe with a dry, absorbent cloth. Use CRC Duster™ to accelerate drying time.
  5. Do not use on plastics – especially modern plastics such as LEXAN®, ABS and Nylon. If uncertain, check with equipment manufacturer.
  6. Not for use on sensitive electronics, computers, tape decks or VCRs. Use a CRC Precision Cleaner.
  7. Use caution when using on or around Energized Equipment. See Electrical Shock Hazard.
- All used and unused product should be disposed of in conformance with local, state and federal regulations.  
For additional information, consult the Material Safety Data Sheet for this product.



00A  
Made in U.S.A.  
CRC#491G

- SAFETY SOLVENT designed to quickly dissolve grease, oil and sludge.
  - NON-FLAMMABLE, chemically stable, non-conductive and non-corrosive.
  - VOC EXEMPT and does not contain Ozone Depleting Substances.
  - EVAPORATES RAPIDLY without residue.
  - HELPS IMPROVE EQUIPMENT PERFORMANCE by removing grease, oil, wax, dirt, carbon and other contaminants from parts and machinery.
  - HIGH DIELECTRIC STRENGTH OF 37,500 volts.
  - AUTHORIZED BY USDA for use in federally inspected meat and poultry plants.
  - MATERIAL SAFETY DATA SHEET printed on back of label for your convenience and safety. (The CRC® MSDL™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827).
- ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Do not touch can to live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from electrical shock.



No. 03180T  
Net Wt. 1 lb. 3 oz. (539 g)

**DANGER: VAPOR HARMFUL. CONTENTS UNDER PRESSURE.**  
Read warnings on back panel.

©2000 CRC Industries, Inc., Warminster, PA 18974

Quick Clean™  
00A

Part # 03180T  
Net Wt. 1 lb. 3 oz. (539 g)  
215-442-8260 (MSDS)

www.crcindustries.com

DANGER: VAPOR HARMFUL. CONTENTS UNDER PRESSURE.



Industrial

**Quick  
Clean™**

**Safety Solvent  
and Degreaser**

**VOC Exempt  
Non-Flammable  
Fast Evaporation  
Leaves No Residue  
Dissolves Grease and Oil**