

CRC Chute Lube® Silicone Lubricant

DIRECTIONS: Read entire label before using this product.

1. Do not apply while equipment is energized. 2. Spray in light, even coats to chutes, dead plates and rails requiring lubrication or moisture protection. 3. Repeat step 2 until adequate lubrication or protection is achieved. Use only the necessary amount to achieve results. 4. Re-apply as needed to maintain performance.

INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto.

1. No aplique el producto mientras el equipo esté conectado. 2. Rocíe en capas ligeras y parejas sobre tolvas, soleras de horno y rieles que requieren lubricación. 3. Repita el paso 2 hasta alcanzan la lubricación o protección adecuada. 4. Aplique nuevamente, según sea necesario, para mantener el rendimiento.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.



Precautionary Statements: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container. Do not pierce or burn, even after use. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Do not breathe gas, mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

Contains Liquefied petroleum gas (68476-86-8), Hydrotreated light naphtha (64742-49-0), Dimethylpolysiloxane (63148-62-9), Hydrotreated light distillates (64742-47-8) and n-Hexane (110-54-3). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación ocular. Puede irritar las vías respiratorias. Puede provocar somnolencia o vértigo. Susceptible de perjudicar la fertilidad. Puede provocar daños en los órganos tras exposiciones prolongadas o repetidas.

Consejos de prudencia: Recabar instrucciones especiales antes de su uso. No manipular antes de haber leído y comprendido todas las precauciones de seguridad. Mantener lejos de calor/chispas/llamas al descubierto/superficies calientes. - No fumar. No rocíe sobre una llama abierta u otra fuente de ignición. No aplique el producto sobre un equipo conectado. Recipiente presurizado: No perforar ni quemar, aun después del uso. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar al producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. No respire gas, neblina o vapor. Usar guantes /indumentaria protectora/equipo de protección para los ojos/la cara. Lavarse las manos cuidadosamente después de la manipulación. Almacenar en lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a temperaturas superiores a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. No provoque vómitos. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGIA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si persiste la irritación de los ojos: Busque atención médica. En caso de exposición demostrada o supuesta: consultar a un médico.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata conduce la electricidad. Mantenga fuera del alcance de todas las fuentes eléctricas vivas, incluso bornes de baterías, solenoides, tableros eléctricos y otros componentes electrónicos. Pasar por alto esta advertencia puede derivar en lesiones graves provocadas por fuego explosivo y/o descarga eléctrica.

©2015 CRC Industries, Inc., 885 Louis Dr., Warminster, PA 18974 Made in U.S.A. 15A CRC# 685B/C
800-321-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS) www.crcindustries.com



Chute Lube® Silicone Lubricant Lubricante de Silicona

Reduces Friction
Helps Packages Slide Easier
Wide Temperature Range

Reduce la Fricción
Ayuda a los Paquetes más Fácil Deslizarse
Amplio Rango de Temperaturas



Nonfood Compounds
Program Listed
Category Code: H2
Reg.# 130031



DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CAUSES EYE IRRITATION. CONTENTS UNDER PRESSURE. KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

PELIGRO: INFLAMABLE. SU INGESTIÓN ES PERJUDICIAL O MORTAL. PROVOCA IRRITACIÓN OCULAR. CONTENIDO BAJO PRESIÓN. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.



No. 03204
Net Wt. / Peso Neto
11 oz (312 g)

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y dobléla hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: Chute Lube® Silicone Lubricant

Product code 03204

Recommended use Lubricant for package handling chutes

Restrictions None known.

Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards	Flammable aerosols (Category 1) Gases under pressure (Liquefied gas)
Health hazards	Serious eye damage/eye irritation (Category 2B) Reproductive toxicity (Category 2 fertility) Specific target organ toxicity, single exposure (Category 3 respiratory tract irritation) Specific target organ toxicity, single exposure (Category 3 narcotic effects) Specific target organ toxicity, repeated exposure (Category 2) Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%
Liquefied petroleum gas	68476-86-8	60 – 70
Hydrotreated light naphtha	64742-49-0	30 – 40
Dimethylpolysiloxane	63148-62-9	1 – 3
Hydrotreated light distillates	64742-47-8	1 – 3
n-Hexane	110-54-3	1 – 3

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects Symptoms may include tearing, redness, swelling, and discomfort.

Vapors have a narcotic effect and may cause headache, fatigue, dizziness, drowsiness and nausea.

Special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media Water.

Unsuitable extinguishing media None known.

Specific hazards Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand, earth or other absorbent material (e.g. cloth, fleece) and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

7. Handling and storage

Handling When using, do not eat, drink or smoke. Do not breathe gas, mist or vapor. Avoid contact with skin and eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains.

Storage Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Store in a well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value
n-hexane	TWA	50 ppm
Hydrotreated light distillates	TWA	100 mg/m ³

Appropriate engineering controls Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection Wear protective gloves such as nitrile, PVC, or Viton®. Wear appropriate clothing to prevent skin contact.

Respiratory protection Wear positive pressure self-contained breathing apparatus (SCBA).

9. Physical and chemical properties

Appearance Light yellow liquid.

Odor threshold Not available.

Melting point/freezing point -72 °F (-58 °C)

Flash point < 0 °F (-18 °C) Tag Closed Cup

Explosive limit - lower (%) 0.6

Vapor pressure 3226 hPa

Relative density 0.68

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 457 °F (236 °C)

Viscosity Not available.

Odor Petroleum.

pH Not available.

Initial boiling point 118 °F (48 °C)

Evaporation rate Fast.

Explosive limit - upper (%) 8.0

Vapor density > 1 (Air = 1)

Solubility(ies) Not available.

Decomposition temperature Not available.

VOC (Weight %): 95% (5.4 lbs/gal, 648.8 g/l)

10. Stability and reactivity

Reactivity Non-reactive

Chemical stability Stable

Possibility of hazardous reactions No

Conditions to avoid Heat, flames and sparks. Temperatures exceeding the flash point. Incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Carbon oxides.

11. Toxicological information

Information on likely routes of exposure:

Ingestion May be fatal if swallowed and enters airways.

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause irritation to the respiratory system. May cause damage to organs by inhalation.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact Causes eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include tearing, redness, and discomfort. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects:

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.

Respiratory sensitization Not available.

Skin sensitization Not expected to cause skin sensitization.

Carcinogenicity Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

Reproductive toxicity Suspected of damaging fertility.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions The dispensed liquid product is a RCRA hazardous waste.

Hazardous waste code D001: Waste Flammable liquid

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313 n-hexane

See full SDS for additional information

16. Other information

Issue date 10/30/2013

CRC #685B/C

Version # 01