

WARNING: Contains Dichloroethane 422-56-0, Dichloroethane 102 (Proprietary mixtures) and 1,1,2,2-tetrafluoroethane 811-97-2. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in a well-ventilated area. Avoid continuous breathing of vapors and spray mist. Avoid contact with skin and eyes. Overexposure to vapor may cause irritation to eyes and respiratory tract, dizziness and loss of consciousness. With high exposure levels, effects can include central nervous system depression and irregular heartbeats. Deliberate misuse by concentrating and inhaling the contents may be harmful or fatal. This product has no flash or fire point at normal handling temperatures. In high concentrations, this product can be made to burn. Do not apply while equipment is energized or near flame or arc. Make sure equipment is thoroughly dry and vented before retesting. Vapors displace oxygen available for breathing and can cause asphyxiation. Vapors are heavier than air and can collect in low areas, pits, small rooms or other unventilated areas. If ventilation is not adequate, respiratory protection should be used. **FIRST AID:** In case of eye and skin contact, flush with water for 15 minutes. If swallowed, may be harmful or fatal. Do not induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately. For Additional Information, Consult MSDS for this product.

KEEP AWAY FROM CHILDREN

To View M.S.D.S.: Tear (DO NOT CUT) label by running a fingernail down between perforations, removing this tab. Fold back label. Do not remove until can is empty.

- DIRECTIONS:** Read entire label before using this product.
1. Spray until clean. Use extension tube for pinpoint cleaning.
 2. This product is safe on most plastics but should be tested on a small area before use.
 3. Use an abrasive on surfaces with heavy carbon deposits or corrosion - remove residue with intermittent spray before reactivating system.
 4. Periodic planned maintenance prolongs life expectancy of components and helps eliminate deposits that cause leakage. Use resistance measurements to determine frequency of application.
 5. If removing Krytox[®], spray until clean and wipe with dry cloth or rag.
 6. For personal safety, do not apply while equipment is energized.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

ALL USED AND UNUSED PRODUCT SHOULD BE DISPOSED OF IN CONFORMANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.



Industrial Precision Plus™ cleaner

**Safe On Most Plastics
Non-Flammable
Fast Evaporation
No Residue
Removes KRYTOX[®]**



**No. 03210
Net Wt. 14 oz. (397 g)**

**WARNING: VAPOR HARMFUL. EYE IRRITANT.
CONTENTS UNDER PRESSURE.**
Read warnings on back panel.

03B
Made in U.S.A.
CRC #413B-C

©2003 CRC Industries, Inc., Warminster, PA 18974
Part # 03210 03B
Precision Plus™ Cleaner
www.crcindustries.com
25 (42-628) (MSDS)
800-521-3168 (Technical Information)
800-272-4520 (Customer Service)
CRC#413B-C

**WARNING: VAPOR HARMFUL. EYE IRRITANT.
CONTENTS UNDER PRESSURE.**