



Industrial

Electronic Degreaser

**Advanced Technology Formula
Non-Chlorinated
HCFC and CFC Alternative
No Flash Point
No Residue**

Part No. 03217

Net Contents: 1 gal. (3.78L)



Nonfood Compounds Program Listed
Category Code: K2 Reg.# 126507

WARNING: VAPOR HARMFUL.

Read warnings on back panel.

CRC *Electronic Degreaser*

- Advanced Technology
- Does not contain CFCs, HCFCs or Chlorinated Solvents
- High Purity formula evaporates quickly and leaves no residue
- Instantly removes grease, oil, dirt, fluxes and polar soils and other contaminants
- Chemically stable, non-conductive and non-corrosive with no flash point
- Helps prevent contact failure or malfunction by dissolving and rinsing away contaminants

WARNING: Contains 1-Bromopropane 106-94-5, C02ol® 202 (Proprietary mixture), t-Butanol 75-65-0, and 1,2-Butylene Oxide 106-88-7. This product has no flash or fire point but has a flammable range if certain concentrations of vapors are exposed to a high energy source. Do not use on energized equipment or near flames or welding arcs. When exposed to extreme heat, vapors may decompose to corrosive and toxic gases such as hydrogen bromide. Make sure equipment is thoroughly dry and vented before restarting. Avoid continuous breathing of vapor. Avoid contact with skin and eyes. Overexposure to vapors can cause eye and skin irritation, irritation to upper respiratory tract, central nervous system effects, irregular heartbeats, unconsciousness and possibly death. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Vapors are heavier than air and can collect in low areas, pits, small rooms and other unventilated areas. If ventilation is not adequate, respiratory protection should be used.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately.
Note to physician: Overexposure will cause symptoms of narcosis and may temporarily increase cardiac irritability.

KEEP AWAY FROM CHILDREN

HMIS: Health: 2 Flammability: 0 Reactivity: 0 PPE: B

DIRECTIONS: *Read entire label before using this product.*

1. For personal safety, do not apply while equipment is energized.
2. Do not use on modern plastics such as LEXAN®, ABS and Noryl. If uncertain, check with manufacturer or test on a small area before using.
3. Do not use on sensitive electronic equipment such as tape decks, VCRs, DVDs, computers, fax machines, copiers, printers, shredders, etc.
4. Spray or brush contaminated areas and allow a few minutes to penetrate and loosen grease and oil-related soil. Repeat application until area is clean and dry.
5. Use an abrasive on surfaces with heavy carbon deposits or corrosion to remove residue with intermittent spray before reactivating system.
6. Periodic planned maintenance prolongs life expectancy of components and helps eliminate deposits that cause leakage. Use resistance measurements to determine frequency of application.

HANDLING AND SPILL PRECAUTIONS: Keep container closed when not in use. Wash thoroughly after handling. Do not enter where high vapor concentrations are suspected unless air-supplied respirator is used and a trained observer is present and equipped with rescue gear. Do not store above 100 F. For spill clean-up, use proper protective equipment. Use absorbent and store in closed containers for proper disposal.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. Do NOT dump in sewers, on the ground, or into any body of water.

For additional information, consult the Material Safety Data Sheet for this product.

**NOT FOR RETAIL SALE.
NOT LABELED FOR USE IN CALIFORNIA.**

©2009 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Tech. Information)
800-272-4620 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
Made in U.S.A. CRC#658 09A

