



Part 3224 Rev 03A

WARNING: Contains Petroleum Distillate 64742-47-8, Carbon Dioxide 124-38-9, Paraffin wax 8002-74-2, Polyester NJTS# 800967-5543. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is flammable and should be kept from flames and other ignition sources. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to vapor may cause irritation to the eyes and respiratory tract, headaches, dizziness, asthma, drowsiness, unconsciousness, and other central nervous system effects. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Vapors are heavier than air and can collect in low areas. **FIRST AID:** In case of eye and skin contact, flush with water for 15 minutes. If swallowed, may be harmful or fatal. Do not induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately.

KEEP AWAY FROM CHILDREN

To review Emergency M.S.D.S.: Tear (DO NOT CUT) label along these two perforations and fold back label. Do not remove label until can is empty.

Directions: Read entire label before using this product.

1. Spray in light, even coats to lubricate and protect metal surfaces.
 2. Apply liberally and allow to penetrate minute openings and free corroded parts.
 3. To displace moisture: Spray wet surfaces until run-off is clear and moisture-free.
 4. Do not apply while equipment is energized.
- All used and unused product should be disposed of in conformance with local, state and federal regulations.
For additional information, consult the Material Safety Data Sheet for this product.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

HMS: Health: 1 Flammability: 2 Reactivity: 0 PPE: B



03A
CRC#559
Made in U.S.A.

- **THIN,** non-staining dry film protects indoors for up to 9 months.
- **PENETRATES** deep into the most minute openings to seal out harmful moisture and prevent corrosion.
- **RESISTS** oil, dirt and dust build-up.
- Contains no CFC's or any chlorinated solvents.
- Ideal for use on precision instruments, gauges and other delicate instruments.
- Meets MIL-C-16173D Grade 3.
- **MEETS** 1998 USDA guidelines for use in federally inspected meat and poultry plants.
- **MATERIAL SAFETY DATA SHEET** printed on back of label for your convenience and safety. (The CRC® MSDS™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827).



No. 03224
Net Wt. 11oz. (312 g)

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. Read warnings on back panel.

SP-250™

- Dry Film Lubricant**
- Displaces Moisture**
- Prevents Corrosion**
- Resists Oil and Dirt Build-up**

©2003 CRC Industries, Inc., Warminster, PA 18974
 CRC#559
 215-442-6260 (MSDS)
 800-272-3169 (Customer Service)
 Part # 03224
 Net Wt. 11 oz. (312 g)
 www.crcindustries.com
 SP-250™
 03A

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE.