

CRC SP-350™

DIRECTIONS: Read entire label before using this product. 1. Do not apply while equipment is energized. 2. Shake can well before use. 3. Spray a light, even coat on surfaces to be protected. 4. Use extension tube for hard to reach areas and for spot lubrication. 5. Thin, non-drying film may be removed with petroleum solvents.

INSTRUCCIONES: Lea toda la etiqueta antes de usar este producto. 1. No aplique el producto mientras el equipo está conectado. 2. Agite bien antes de usar. 3. Rocíe con una capa liviana y pareja sobre las superficies a proteger. 4. Utilice el tubo de extensión para alcanzar las áreas difíciles y para lubricar partes. 5. La película delgada que no se seca puede ser eliminada con solventes para petróleo.

Danger: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin and serious eye irritation. May cause drowsiness or dizziness.



Precautionary Statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container. Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing gas, mist or vapor. Wash hands thoroughly after handling. Wear protective gloves and eye/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

First Aid: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Contains Hydrotreated light distillates (64742-47-9). Solvent-refined heavy paraffinic distillates (64741-89-4). Standard solvent (6052-41-3), n-Butyl stearate (123-95-5), Carbon dioxide (124-39-9), Fatty acids (61788-89-4), Petroleum (6009-03-8), Sodium petroleum sulfonate (68008-26-4), Medium aliphatic solvent naphtha (64742-88-7), n-Nonane (111-84-2) and n-Octane (111-65-9). Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

Electrical Shock Hazard: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Peligro: Aerosol extremadamente inflamable. Contiene gas a presión; puede explotar si se calienta. Puede ser mortal en caso de ingestión y de penetración en las vías respiratorias. Provoca irritación cutánea y ocular grave. Puede provocar somnolencia o vértigo.

Consejos de prudencia: Mantener lejos de calor/chispas/llamas al descubierto/superficies calientes. - No fumar. No rocíe sobre una llama abierta u otra fuente de ignición. No aplique el producto sobre un equipo conectado. Recipiente presurizado: No perforar ni quemar, aun después del uso. Apague todas las llamas, pilotos y calefactores. El vapor se acumulará rápidamente y puede inflamarse. Utilice solo con ventilación adecuada; mantenga la ventilación durante la utilización del producto hasta que el vapor haya desaparecido. Abra las puertas y ventanas y utilice otros medios para asegurar la provisión de aire fresco al utilizar el producto y mientras se esté secando. Si presenta algunos de los síntomas enumerados en esta etiqueta, aumente la ventilación o deje el área. No respirar gas, niebla o vapor. Lávase las manos cuidadosamente después de la manipulación. Usar guantes de protección y equipo para proteger los ojos /la cara. Almacenar en lugar bien ventilado. Guardar bajo llave. Proteger de la luz solar. No exponer a temperaturas superiores a 50 °C/122 °F. La exposición a altas temperaturas puede provocar que la lata estalle. Eliminación de contenidos / contenedor en consonancia con los reglamentos locales / regionales / nacionales pertinentes.

Primeros Auxilios: En caso de ingestión: Llamar inmediatamente a un centro de toxicología o a un médico. No provoque vómitos. En caso de contacto con la piel: Lavar con abundante agua. Si ocurre irritación de la piel: Busque atención médica. Quitar la ropa contaminada y lavarla antes de volver a usarla. En caso de inhalación: Transportar la persona al aire libre y mantenerla en una posición que le facilite la respiración. Llamar a un CENTRO DE TOXICOLOGIA o a un médico si la persona se encuentra mal. En caso de contacto con los ojos: Enjuagar con agua cuidadosamente durante varios minutos. Quitar las lentes de contacto cuando estén presentes y pueda hacerse con facilidad. Proseguir con el lavado. Si persiste la irritación de los ojos: Busque atención médica.

Su mal uso deliberado, concentrando e inhalando su contenido es ilegal y puede ser perjudicial o fatal. La inhalación abusiva puede causar la muerte. Para mayor información, consulte la Hoja de Datos de Seguridad para este producto.

Peligro de Descarga Eléctrica: Esta lata conduce la electricidad. Mantenga fuera del alcance de todas las fuentes eléctricas vivas, incluso hornos de baterías, solenoides, tableros eléctricos y otros componentes electrónicos. Pasar por alto esta advertencia puede derivar en lesiones graves provocadas por fuego explosivo y/o descarga eléctrica.

©2015 CRC Industries, Inc., 835 Louis Dr., Warminster, PA 18974 Made in U.S.A. 15A CRC# 527/J/K
800-521-3168 (Technical Information) • 800-272-4620 (Customer Care) • 215-442-6260 (SDS) www.crcindustries.com



SP-350™

Corrosion Inhibitor

Inhibidor de Corrosion

Long Term Lubricant
and Rust Preventative

Lubricante a Largo Plazo que
Previene la Formación de Óxido



Nonfood Compounds
Program Listed
Category Code: H2
Reg.# 017409



DANGER: FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
EYE AND SKIN IRRITANT.
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.
Read warnings on back panel.

PELIGRO: INFLAMABLE.
SU INGESTIÓN ES PERJUDICIAL
O MORTAL. IRRITA LA PIEL
Y LOS OJOS. CONTENIDO BAJO
PRESIÓN. MANTENGA FUERA
DEL ALCANCE DE LOS NIÑOS.
Lea las advertencias en el dorso.



No. 03262
Net Wt./Peso Neto
11 oz (312 g)

To review S.D.S.: Tear (DO NOT CUT) label along these perforations and fold back label. After viewing, reattach label. Do not completely remove label until can is empty. Para revisar la Hoja de Datos de Seguridad (HDS): Rasgue (NO CORTE) la etiqueta siguiendo estas perforaciones y dóblela hacia atrás. Al terminar, vuelva a pegar la etiqueta. No la retire completamente hasta que la lata esté vacía.

1. Identification

Product identifier: SP-350™ Corrosion Inhibitor

Product code: 03262

Recommended use: Lubricant and corrosion inhibitor

Restrictions: None known.

Manufactured or sold by: CRC Industries, Inc., 885 Louis Drive, Warminster, PA 18974

Phone: 215-674-4300

Emergency phone number: CHEMTREC - 24 HOURS: 800-424-9300

2. Hazard(s) identification

Physical hazards: Flammable aerosols (Category 1)

Gases under pressure (Compressed gas)

Health hazards: Skin corrosion/irritation (Category 2)

Serious eye damage/eye irritation (Category 2A)

Specific target organ toxicity, single exposure (Category 3 narcotic effects)

Aspiration hazard (Category 1)

Label elements (see front side of label)

3. Composition/information on ingredients

Hazardous components

Chemical name	CAS number	%	Chemical name	CAS number	%
Hydrotreated light distillates	64742-47-8	30 – 40	Petrolatum	8009-03-8	1 – 3
Solvent-refined heavy paraffinic distillates	64741-88-4	20 – 30	Sodium petroleum sulfonate	68608-26-4	1 – 3
Stoddard solvent	8052-41-3	10 – 20	Medium aliphatic solvent naphtha	64742-88-7	1 – 3
n-Butyl stearate	123-95-5	3 – 5	n-Nonane	111-84-2	< 0.3
Carbon dioxide	124-38-9	1 – 3	n-Octane	111-65-9	< 0.2
Fatty acids	61788-89-4	1 – 3			

(Specific chemical identity and/or percentage of composition has been withheld as a trade secret.)

4. First-aid measures

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact: Rinse skin with water/shower. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion: Call a physician or poison control center immediately. Rinse mouth.

Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects: Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness, drowsiness and nausea.

Special treatment needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media: Alcohol resistant foam. Water. Water spray. Dry powder. Dry chemicals. Carbon dioxide (CO₂).

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards: Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions: Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Containment and cleaning up: Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand, earth or other absorbent material (e.g. cloth, fleece) and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

7. Handling and storage

Handling: Pressurized container. Do not pierce or burn, even after use. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Avoid breathing gas, mist or vapor. Avoid contact with skin and eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

Storage: Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value	Components	Type	Value
Fatty acids	TWA	5 mg/m3	n-Octane	TWA	300 ppm
Carbon dioxide	TWA	5000 ppm	Petrolatum	TWA	5 mg/m3
Solvent-refined heavy paraffinic distillates	TWA	5 mg/m3	Stoddard solvent	TWA	100 ppm
n-Nonane	TWA	200 ppm	n-Butyl stearate	TWA	10 mg/m3

Appropriate engineering controls: Mechanical ventilation or local exhaust ventilation is recommended.

Individual protection measures:

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin protection: Wear protective gloves such as neoprene or nitrile. Wear appropriate clothing to prevent skin contact.

Respiratory protection: Wear positive pressure self-contained breathing apparatus (SCBA).

9. Physical and chemical properties

Appearance: Tan creamy liquid.

Odor threshold: Not available.

Melting point/freezing point: -94 °F (-70 °C)

Flash point: 144 °F (62 °C) Tag Closed Cup

Explosive limit - lower (%) 0.5

Vapor pressure: 859 hPa

Relative density 0.87

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature: 410 °F (210 °C)

Decomposition temperature: Not available.

VOC (Weight %): 24.5% (1.7 lbs/gal, 206.0 g/l)

Odor: Petroleum.

pH: Not available.

Initial boiling point: 315 °F (157 °C)

Evaporation rate: Slow

Explosive limit - upper (%) 6

Vapor density > 1 (Air = 1)

Solubility(ies) Not available.

Viscosity: Not available.

10. Stability and reactivity

Reactivity: Non-reactive

Chemical stability: Stable

Possibility of hazardous reactions: No

Conditions to avoid: Heat, flames and sparks. Temperatures exceeding the flash point. Incompatible materials.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Carbon oxides. Sulfur compounds.

11. Toxicological information

Information on likely routes of exposure:

Ingestion: May be fatal if swallowed and enters airways.

Inhalation: Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.

Skin contact: Causes skin irritation.

Eye contact: Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics: Symptoms may include stinging, tearing, redness, swelling, pain and blurred vision. Skin irritation.

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects:

Acute toxicity: May be fatal if swallowed and enters airways. Narcotic effects.

Respiratory sensitization: Not available.

Skin sensitization: Not expected to cause skin sensitization.

Carcinogenicity: Not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA.

Reproductive toxicity: This product is not expected to cause reproductive or developmental effects.

Aspiration hazard: May be fatal if swallowed and enters airways.

Chronic effects: Prolonged inhalation may be harmful.

12. Ecological information

See full SDS for additional information

13. Disposal considerations

Disposal instructions: The dispensed liquid product is not a RCRA hazardous waste.

Hazardous waste code: Not regulated.

14. Transport information

DOT shipping description: UN1950, Aerosols, flammable, 2.1, limited quantity

15. Regulatory information

SARA 313: None.

See full SDS for additional information

16. Other information

Issue date: 4/14/2015

CRC #527/JK

Version # 02