




Nonfood Compounds Program
Listed (H2) (#135818)

Industrial SP-350™

Corrosion Inhibitor



Part No. 03268

NET WEIGHT 379.5 lbs (172 kg)



DANGER

Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation.
Causes serious eye irritation. May cause drowsiness or dizziness.

Mix Well Before Using

- Protects metal up to 2 years indoors.
- Unique overlapping plating action provides extended protection to both edges and flat surfaces.
- Thin, non-drying film provides excellent protection during shipment and storage.

PRECAUTIONARY STATEMENTS

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash hands thoroughly after handling. Wear protective gloves/eye protection/face protection. Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations.

FIRST AID

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	2	REACTIVITY	0
FLAMMABILITY	2	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

Contains Hydrotreated light distillates (64742-47-8), Solvent-refined heavy paraffinic distillates (64741-88-4), n-Butyl stearate (123-95-5), Fatty acids (61788-89-4), Petrolatum (8009-03-8), Sodium petroleum sulfonate (68608-26-4) and n-Octane (111-65-9).

©2013 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical information)
800-272-4620 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
13A CRC#540F/G Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300



Batch No:
Date Code: