

L02622

03303-01A

WARNING: Contains Paintable Silicone Fluid 68037-77-4, 1-Chloro-1,1-difluoroethane 75-68-3 and proprietary Propellant Blend. Do not puncture, incinerate, or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in a well ventilated area. Avoid continuous breathing of vapors and moist contact with skin and eyes. Overexposure to vapor may cause irritation to eyes and respiratory tract, dizziness and loss of concentration. With high exposure levels, deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Vapors displace oxygen available for breathing, and can cause asphyxiation. Vapors are heavier than air and can collect in low areas, pits, small rooms or the ventilated area. If ventilation is not adequate, respiratory protection should be used. Death can occur without warning if too much is breathed. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

To view M.S.D.S. Tear (DO NOT CUT) label by running a fingernail down between perforations, removing this tab. Fold back label. Do not remove until can is empty.

Directions: Read entire label before using this product.

1. For best results do not overspray.
 2. Apply a light, even film to mold surface as needed when sticking occurs.
 3. To avoid marked parts, do not over apply.
 4. Do not spray directly on plastics.
 5. Do not use as a plastic polish.
 6. Hold can 10" to 12" from mold surface.
- ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Do not touch can or live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from electrical shock.

- **RAPID DRYING** anti-stick mold release agent suitable for cold and hot molds.
- **COMPLETELY COMPATIBLE** with secondary operations where parts must be painted, stenciled, glued, bonded, laminated, hot stamped or metallized. No special cleaning required before part decoration.
- **3% SOLIDS** provide effective lubrication up to 650°F.
- **BIODEGRADABLE, ODORLESS**, non-staining and non-corrosive.
- **PREVENTS STICKING** to increase the life of dies and molds, improve production surface finishes and reduce production times.
- **EXCELLENT FOR USE** in injection and compression molding of acetal, ABS, acrylic, nylon, polycarbonate, polystyrene, polysulfone and rubber.
- **MATERIAL SAFETY DATA SHEET** printed on back of label for your convenience and safety. (The CRC® MSD[LP]™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827).



01A
Made in U.S.A.



**Fast Drying
Biodegradable
Prevents Sticking
Secondary Operation Compatible**

Mold Release

Paintable

Industrial



**CONTENTS UNDER PRESSURE
DANGER: FLAMMABLE**

©2001 CRC Industries, Inc., Warminster, PA 18974
800-521-8188 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
Net Wt. 11.5 oz. (326 g)
Part # 03303 01A
Paintable Mold Release