

L02622

03304-01A

WARNING: Contains Particulate Silicone Fluid 6803-74-4, Dimethyl Ether 115-10-6 and dichlorofluoroethane 1717-00-6. This product is not defined as flammable by Consumer Product Safety Commission regulations. Product should be kept away from all sources of ignition. Do not puncture, incinerate, or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in a well ventilated area. Avoid continuous breathing of vapors and mist. Avoid contact with skin and eyes. Overexposure to vapor may cause irritation to eyes and respiratory tract. Dizziness and loss of concentration. With high exposure levels, effects can include central nervous system depression and irregular heartbeats (cardiac arrhythmia). Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Vapors displace oxygen available for breathing and can cause asphyxiation. Vapors are heavier than air and can collect in low areas, pits, small corners or the ventilated area. If ventilation is not adequate, respiratory protection should be used. Death can occur without warning. Vapors are heavier than air and can collect in low areas, pits, small corners or the ventilated area. If ventilation is not adequate, respiratory protection should be used. DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

To view M.D.S.S.: Tear (DO NOT CUT) label by running a fingernail down between perforations, removing this tab. Fold back label. Do not remove until can is empty.

Directions: Read entire label before using this product.

1. For best results do not overspray.
2. Apply a light, even film to mold surface as needed when sticking occurs.
3. To avoid marked parts, do not over apply.
4. Hold can 10" to 12" from mold surface.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Do not touch panels and other electronic components. Failure to observe this warning may result in serious injury from electrical shock.

- **RAPID DRYING** anti-stick mold release agent suitable for cold and hot molds.
- **COMPLETELY COMPATIBLE** with secondary operations where parts must be painted, stenciled, glued, bonded, laminated, hot stamped or metalized. No special cleaning required before part decoration.
- **EFFECTIVE TEMPERATURE RANGE** of 35°F to 600°F.
- **5% SOLIDS** provide superior lubrication even in severe molding conditions.
- **BIODEGRADABLE, ODORLESS,** non-staining and non-corrosive.
- **PREVENTS STICKING** to increase the life of dies and molds, improve product surface finishes and reduce production times.
- **EXCELLENT FOR USE** in injection and compression molding of ABS, acetal, acrylic, nylon, polycarbonate, polystyrene, polysulfone and rubber.
- **MATERIAL SAFETY DATA SHEET** printed on back of label for your convenience and safety. (The CRC® MSDL™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827).



01A

Made in U.S.A.



No. 03304

Net Wt. 12 oz. (340 g)

CAUTION: CONTENTS UNDER PRESSURE.

Read warnings on back panel.

©2001 CRC Industries, Inc., Warminster, PA 18974
 800-521-3169 (Technical Information)
 800-272-4620 (Customer Service)
 215-442-6260 (MSDS)
 Heavy Duty Paintable Mold Release
 Part # 03304 01A
 Net Wt. 12 oz. (340 g)
 www.crcindustries.com

CAUTION: CONTENTS UNDER PRESSURE.

CRC®
Industrial
Heavy Duty
Paintable
Mold Release